



**NETGEAR
GS728TPP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**

Model: GS728TPP-300EUS

Manufacturer: NETGEAR

EAN: 606449162356

Product Code: 610157

R10,374

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Noise level: 33.3 dB | Built-in processor: Yes | Processor model: ARM Cortex-A55 | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.1w | Operating relative humidity (H-H): 0 - 90% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Power over Ethernet (PoE) power per port: 380 W | Networking standards: IEEE 802.1D | Power source: AC | Processor manufacturer: ARM | Mean time between

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

failures (MTBF): 1252990 h | Processor frequency: 800 MHz | Depth: 257 mm | Power consumption (typical): 26 W | Switching capacity: 56 Gbit/s | IPv6 routes: 32 | Operating temperature (T-T): 0 - 50 °C | IPv4 routes: 32 | Weight: 4.11 kg | Power consumption (max): 427 W | Flash memory: 64 MB | Product colour: Grey | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Height: 432 mm | Storage temperature (T-T): -20 - 70 °C | Internal memory: 512 MB | Power over Ethernet (PoE): Yes | Width: 440 mm | Rack mounting: Yes | Number of fans: 2 fan(s) | USB Type-A ports quantity: 1 | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Number of VLANs: 256 | DHCP features: DHCP snooping | Redundant fans support: Yes | Access Control List (ACL) IPv4 entries: 100 | MAC address table: 16000 entries | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | ARP inspection: Yes | Switch layer: L2/L3/L4 | Latency (10-100 Mbps): 8.871 µs | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Power over Ethernet plus (PoE+) ports quantity: 24 | Packet buffer memory: 1.5 MB | Multicast support: Yes | DHCP features: DHCPv6 client | Installed SFP modules quantity: 4 | Latency (1 Gbps): 4.701 µs | Switch type: Managed | Access Control List (ACL): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950