



# **NETGEAR GS110TP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey**

Model: GS110TP-300EUS

Manufacturer: NETGEAR

EAN: 606449137644

Product Code: 610160

## **R3,877**

Certification: CE, FCC, VCCI Class B, C-Tick | Supported network protocols: HTTP, HTTPS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 0 - 95% | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Power over Ethernet (PoE) power per port: 55 W | Networking standards: IEEE 802.3ab | IPv4 multicast entries: 32 | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3z | AC input frequency:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

50 - 60 Hz | Access Control List (ACL) IPv6 entries: 100 | LED indicators: LAN | Manual: Yes | Input current: 1.25 A | LED indicators: Power | Power supply included: Yes | Switching protocols: SNMP | Networking standards: IEEE 802.3i | Weight: 610 g | LED indicators: Speed | Mean time between failures (MTBF): 1200041 h | MAC address table: 8000 entries | Operating temperature (T-T): 0 - 40 °C | Port mirroring: Yes | DC input voltage: 54 V | Copper ethernet cabling technology: 10BASE-T | LED indicators: Activity | Access Control List (ACL): Yes | AC input voltage: 100 - 240 V | LED indicators: Link | Switch layer: L2/L3/L4 | Multicast support: Yes | Operating altitude: 0 - 3000 m | Storage temperature (T-T): -20 - 70 °C | Processor frequency: 500 MHz | Packet buffer memory: 0.5 MB | Rate limiting: Yes | Total Power over Ethernet (PoE) budget: 69.5 W | Power consumption (max): 15.1 W | Products per master (outer) case: 6 pc(s) | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Package width: 161 mm | Depth: 101 mm | Product colour: Grey | DHCP features: DHCP client | Switching capacity: 20 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 8 | Height: 27 mm | Number of VLANs: 64 | Package weight: 1.49 kg | Master (outer) case length: 350 mm | Master (outer) case height: 309 mm | LED indicators: PoE | Internal memory: 128 MB | Package depth: 267 mm | Heat dissipation: 237.38 BTU/h | Switch type: Managed | Package height: 86 mm | Number of multicast groups filtered: 256 | Quality of Service (QoS) support: Yes | Package type: Box | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | Non-operating altitude: 0 - 3000 m | Management protocols: SNMP | Operating relative humidity (H-H): 0 - 95% | Full duplex: Yes | SFP module slots quantity: 2 | Master (outer) case gross weight: 9.73 kg | Flow control support: Yes | Memory type: RAM | Master (outer) case width: 274 mm | Power over Ethernet (PoE): Yes | ARP inspection: Yes | Harmonized System (HS) code: 85176990 | IGMP snooping: Yes | Width: 236 mm | Rack mounting: No | Spanning tree protocol: Yes | Store-and-forward: Yes | Broadcast storm control: Yes | Jumbo frames support: Yes | Link aggregation: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950