



NETGEAR 28- Port PoE Gigabit/10G Stackable Smart Switch (GS728TXP)



Model: GS728TXP-300EUS

Manufacturer: NETGEAR

EAN: 606449171068

Product Code: 610162

R10,787

MAC address filtering: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | SSH/SSL support: Yes | Networking standards: IEEE 802.1ab | Product colour: Black | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Flash memory: 64 MB | Basic switching RJ-45 Ethernet ports quantity: 24 | 10G support: Yes | Flow control support: Yes | VLAN support: Yes | Storage temperature (T-T): -20 - 70 °C | Number of VLANs: 256 | Mean time between failures (MTBF):

1252990 h | Operating altitude: 0 - 3000 m | Power consumption (typical): 748.18 W | SFP+ module

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

slots quantity: 4 | Access Control List (ACL): Yes | Networking standards: IEEE 802.3u | Static route: Yes | Non-operating altitude: 0 - 3000 m | Operating temperature (T-T): 0 - 50 °C | Processor frequency: 800 MHz | Weight: 3.8 kg | Cables included: AC | Full duplex: Yes | DHCP features: DHCP client | Packet buffer memory: 16 MB | MAC address table: 16000 entries | Access Control List (ACL) ingress: 100 | Port mirroring: Yes | Number of static routes: 32 | Depth: 257 mm | Width: 440 mm | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | Rack mounting: Yes | Link aggregation: Yes | Rate limiting: Yes | Height: 43.2 mm | Spanning tree protocol: Yes | Manual: Yes | Broadcast storm control: Yes | Switch layer: L2/L3 | Stackable: Yes | Operating relative humidity (H-H): 0 - 95% | Built-in processor: Yes | Noise level: 26.8 dB | Virtual LAN features: Voice VLAN | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950