

NETGEAR 8x1G PoE+ 110W 1x1G and 1xSFP Managed Switch



Model: GSM4210PD-100EUS

Manufacturer: NETGEAR

EAN: 606449160192

Product Code: 610163

R16,649

Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | IPv4 multicast entries: 2000 | Power over Ethernet (PoE): Yes | AC input frequency: 50 - 60 Hz | Multicast support: Yes | Power source: AC/DC | Rack mounting: Yes | Depth: 140 mm | Processor model: ARM Cortex-A9 | Rate limiting: Yes | Processor frequency: 1250 MHz | Power over Ethernet plus (PoE+) ports quantity: 8 | LED indicators: Status | MAC address table: 16000 entries | IGMP snooping: Yes | Switch type: Managed | Operating temperature (T-T): 0 - 50 °C | Power supply included: Yes | Weight: 967 g | Operating altitude: 0 - 3000 m | Width: 210 mm | Heat dissipation: 559.555 BTU/h | LED indicators: PoE | Total Power over Ethernet (PoE) budget: 110 W | DHCP features: DHCP snooping | Basic switching RJ-45 Ethernet ports quantity: 8 | LED indicators: Power | Manual: Yes | Storage temperature (T-T): -20 - 70 °C | Full duplex: Yes | Noise level: 30.06 dB | Height: 40 mm | User guide: Yes | SSH/SSL support: Yes | Internal memory: 2048 MB | Built-in processor: Yes | Loop protection: Yes | Operating relative humidity (H-H): 0 - 90% | Authentication type: RADIUS | Quality of Service (QoS) support: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCP Option 82 | Switch

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

layer: L2/L3 | AC input voltage: 220 - 240 V | Product colour: Black | Authentication: MAC-based authentication | Access Control List (ACL): Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.1D | Non-operating altitude: 0 - 3000 m | Networking standards: IEEE 802.1w | Store-and-forward: Yes | Broadcast storm control: Yes | DHCP features: DHCP server | DHCP features: DHCPv6 server | Link aggregation: Yes | Spanning tree protocol: Yes | DHCP features: DHCPv6 relay | Switching capacity: 24 Gbit/s | DHCP features: DHCP relay | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bt | BPDU filtering/protection: Yes | DHCP features: DHCPv6 client

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950