



Ubiquiti Pro Max 48 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Model: USW-Pro-Max-48

Manufacturer: UBIQUITI

EAN: 810084692745

Product Code: 610177

R14,785

DHCP features: DHCP snooping | Switch layer: L3 | VLAN support: Yes | Form factor: 1U | Reset button: Yes | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | LED indicators: Speed | DHCP features: DHCP relay | Loop protection: Yes | SFP+ module slots quantity: 4 | LED indicators: Status | Warnings: Follow the safety guidelines for electrical current. | AC input voltage: 100 - 240 V | LED indicators: Link | Basic switching RJ-45 Ethernet ports quantity: 48 | LED indicators: Network | Stackable: Yes | Networking standards: IEEE 802.1x | Power over Ethernet (PoE): No | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 32 | IGMP snooping: Yes | Width: 442.4 mm | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Height: 43.7 mm | Rack mounting: Yes | Power consumption (max): 100 W | Compliance certificates: CE | Throughput: 112 Gbit/s | Cables included: Power | Compliance certificates: Federal Communications Commission (FCC) | Depth: 325 mm | Virtual LAN features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Voice VLAN | Weight: 4.8 kg | Switching capacity: 224 Gbit/s | Operating temperature (T-T): -5 - 40 °C
| Forwarding rate: 166.656 Mpps | Power connector: AC/DC | Compliance certificates: Industry
Canada (IC) | Jumbo frames support: Yes | Power source: AC/DC | Mounting brackets included: Yes |
Product colour: Grey | Rate limiting: Yes | 10G support: Yes | Flow control support: Yes | Operating
relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Port mirroring: Yes | Display type:
LCM | Power supply included: Yes | Static route: Yes | 2.5G Ethernet (copper) ports quantity: 16

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950