



Ubiquiti UniFi Pro 24-Port PoE Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Silver

Model: USW-Pro-24-POE

Manufacturer: UBIQUITI

EAN: 817882027649

Product Code: 610185

R15,862

Certification: CE, FCC, IC | Form factor: 1U | Rack mounting: Yes | Reset button: Yes | Width: 442.4 mm | Height: 43.7 mm | AC input frequency: 50 - 60 Hz | Operating temperature (T-T): -5 - 40 °C | Display type: LCM | Power consumption (max): 450 W | Total Power over Ethernet (PoE) budget: 400 W | Operating relative humidity (H-H): 10 - 90% | Weight: 4.3 kg | Depth: 285.4 mm | Power over Ethernet (PoE): Yes | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: System | LED indicators: PoE | LED indicators: Speed | LED indicators: Activity | Power source: AC | Networking standards: IEEE 802.3af | Redundant power supply (RPS) support: Yes | Quality of Service (QoS) support: Yes | Product colour: Silver | Web-based management: Yes | Networking standards: IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

802.3at | Forwarding rate: 65.472 Mpps | Switching capacity: 88 Gbit/s | IGMP snooping: Yes | MAC address table: 16000 entries | Basic switching RJ-45 Ethernet ports quantity: 24 | Static route: Yes | Authentication type: IEEE 802.1x, RADIUS | Packet buffer memory: 2 MB | Power supply included: Yes | VLAN support: Yes | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 16 | Harmonized System (HS) code: 85176990 | Switch type: Managed | SFP+ module slots quantity: 2 | DHCP features: DHCP snooping | Full duplex: Yes | Warnings: Make sure the ventilation of the equipment is not blocked. | Number of power supply units: 1 | Rate limiting: Yes | System event log: Yes | Number of VLANs: 1000 | Warnings: Follow the safety guidelines for electrical current. | Power over Ethernet (PoE) power per port: 64 W | Warnings: Avoid contact of the device with liquid. | Switch layer: L2/L3 | Throughput: 44000 Mpps | 10G support: Yes | DHCP features: DHCP relay | Power over Ethernet 4PPoE (PoE++) ports quantity: 8 | DHCP features: DHCP server | IPv4 routes: 64 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Port mirroring: Yes | Jumbo frames support: Yes | Link aggregation: Yes | Flow control support: Yes | Broadcast storm control: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950