



**Ubiquiti USW-
PRO-MAX-48-
POE network
switch L3 2.5G
Ethernet
(100/1000/2500)
Power over
Ethernet (PoE)
Grey**

Model: USW-Pro-Max-48-PoE

Manufacturer: UBIQUITI

EAN: 810084692721

Product Code: 610193

R28,855

Reset button: Yes | Power consumption (max): 820 W | Networking standards: IEEE 802.1x | Form factor: 1U | Weight: 6.2 kg | Cables included: Power | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Height: 43.7 mm | Product colour: Grey | Quality of Service (QoS) support: Yes | Depth: 399.6 mm | AC input voltage: 100 - 240 V | Power source: AC | Manual: Yes | LED indicators: System | Operating temperature (T-T): -5 - 40 °C | Total Power over Ethernet (PoE) budget: 720 W | Operating relative humidity (H-H): 10 - 90% | Width: 442.4 mm | AC input frequency:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

50/60 Hz | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Display type: LCM | Power over Ethernet (PoE) voltage: 57 V | SFP+ module slots quantity: 4 | Heat dissipation: 341.2 BTU/h | Switch type: Managed | Virtual LAN features: Voice VLAN | DHCP features: DHCP server | Switch layer: L3 | Flow control support: Yes | Power over Ethernet plus (PoE+) ports quantity: 32 | Throughput: 112 Gbit/s | Switching capacity: 224 Gbit/s | Power connector: AC-in jack | Forwarding rate: 167 Mpps | Basic switching RJ-45 Ethernet ports quantity: 48 | 10G support: No | Number of VLANs: 1000 | Rack mount kit: Yes | Loop protection: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCP guarding | MAC address table: 32000 entries | Gigabit Ethernet (copper) ports quantity: 32 | Port mirroring: Yes | Packet buffer memory: 2 MB | VLAN support: Yes | DHCP features: DHCP relay | Power over Ethernet (PoE) power per port: 15.4 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | IGMP snooping: Yes | Broadcast storm control: Yes | Backlight display: Yes | Power over Ethernet (PoE) type supported: PoE+ | Warnings: Avoid contact of the device with liquid. | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Jumbo frames support: Yes | Sustainability compliance: Yes | Rate limiting: Yes | Static route: Yes | Power supply included: Yes | Power over Ethernet 4PPoE (PoE++) ports quantity: 16 | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | IPv4 routes: 12000 | Compliance certificates: CE | 2.5G Ethernet (copper) ports quantity: 16 | Compliance certificates: National Defense Authorization Act (NDAA)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950