

Digitus 1D Barcode Hand Scanner



Model: DA-81001

Manufacturer: DIGITUS

EAN: 4016032473633

Product Code: 610602

R932

Compatible operating systems: Mac/Linux | Warnings: Avoid direct contact with eyes. | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Sensor type: Linear | Depth: 87 mm | Power source type: USB | Harmonized System (HS) code: 84716070 | Power consumption: 100 mA | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | International Protection (IP) code: IP54 | Linear (1D) barcodes supported: ITF-6 | Linear (1D) barcodes supported: Code 32 | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5 | Scanner type: 1D | Mobile operating systems supported: iOS | Housing material: Polycarbonate (PC) | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Weight: 110 g | 2D (matrix & stacked) barcodes supported: Not supported | Mobile operating systems supported: Android | Country of origin: China | Light source: 650 nm | Type: Handheld bar code reader | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: EAN 128 | Linear (1D) barcodes supported: MSI | Connectivity technology: Wired | Housing material: Acrylonitrile butadiene styrene (ABS) | Tilt reading angle: -45 - 45° | Input voltage: 5 V | Height: 165 mm | Storage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

temperature (T-T): -40 - 70 °C | Width: 63 mm | Product colour: Black | Cable length: 2 m | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Windows operating systems supported: Yes | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: IATA | Standard interfaces: RJ-45, USB | Operating temperature (T-T): -20 - 50 °C | Maximum scan width: 30 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950