



Digitus 2D Barcode Hand Scanner, QR- Code Compatible



Model: DA-81002

Manufacturer: DIGITUS

EAN: 4016032473640

Product Code: 610603

R1,161

Compatible operating systems: Mac/Linux | Power consumption: 120 mA | Power source type: USB | 2D (matrix & stacked) barcodes supported: QR Code | Depth: 87 mm | Height: 165 mm | Windows operating systems supported: Yes | Light source: 650 nm | Type: Handheld bar code reader | Maximum scan width: 10 cm | Sensor type: CMOS | Standard interfaces: RJ-45, USB | International Protection (IP) code: IP54 | Connectivity technology: Wired | Weight: 120 g | 2D (matrix & stacked) barcodes supported: PDF417 | Scanner type: 1D/2D | Country of origin: China | Housing material: Polycarbonate (PC) | Housing material: Acrylonitrile butadiene styrene (ABS) | Operating temperature (T-T): -20 - 50 °C | 2D (matrix & stacked) barcodes supported: Data Matrix | Width: 63 mm | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Mobile operating systems supported: iOS | Warnings: Avoid direct contact with eyes. | Linear (1D) barcodes supported: MSI | Cable length: 2 m | Harmonized System (HS) code: 84716070 | Product colour: Black | Linear (1D) barcodes supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

GS1-128 (UCC/EAN-128) | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: EAN 128 | Linear (1D) barcodes supported: Code 32 | Mobile operating systems supported: Android | Read rate (max): 200 reads/s | Linear (1D) barcodes supported: ITF-6 | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: IATA | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Tilt reading angle: -60 - 60° | Storage temperature (T-T): -40 - 70 °C | Input voltage: 5 V | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950