



Digitus 2D Barcode Hand Scanner, Battery- Operated, Bluetooth & QR- Code Compatible



Model: DA-81003

Manufacturer: DIGITUS

EAN: 4016032473657

Product Code: 610604

R1,679

Compatible operating systems: Mac | Product colour: Black | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 32 | Mobile operating systems supported: Android | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Mobile operating systems supported: iOS | Cable length: 2 m | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | Battery type: Built-in battery | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5 | Linear (1D) barcodes supported: GS1 DataBar | Height: 165 mm | Linear (1D) barcodes supported: GS1-128

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(UCC/EAN-128) | Windows operating systems supported: Yes | Battery capacity: 2000 mAh | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: ITF-6 | Storage temperature (T-T): -40 - 70 °C | Operating system installed: Linux | Connectivity technology: Wired | Operating temperature (T-T): -20 - 50 °C | Maximum scan width: 10 cm | Standard interfaces: Bluetooth, RJ-45, USB | Country of origin: China | Read rate (max): 200 reads/s | Width: 63 mm | Harmonized System (HS) code: 84716070 | Scanner type: 1D/2D | Sensor type: CMOS | 2D (matrix & stacked) barcodes supported: PDF417 | 2D (matrix & stacked) barcodes supported: QR Code | Type: Handheld bar code reader | Tilt reading angle: -60 - 60° | Depth: 87 mm | 2D (matrix & stacked) barcodes supported: Data Matrix | Housing material: Polycarbonate (PC) | Input voltage: 5 V | Housing material: Acrylonitrile butadiene styrene (ABS) | International Protection (IP) code: IP54 | Battery technology: Lithium-Ion (Li-Ion) | Weight: 150 g | Power consumption: 120 mA | Light source: 650 nm | Power source type: Battery | Linear (1D) barcodes supported: IATA | Linear (1D) barcodes supported: EAN 128 | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Warnings: Avoid direct contact with eyes. | Battery life: 18 h

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950