



Zebra DS2208 Handheld bar code reader 1D/2D LED Black



Model: DS2208-SR7U2100SGW

Manufacturer: ZEBRA

EAN:

Product Code: 610611

R2,430

Sustainability certificates: RoHS | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MaxiCode | 2D (matrix & stacked) barcodes supported: PDF417 | Operating temperature (T-T): 0 - 50 °C | Linear (1D) barcodes supported: Codabar | Connectivity technology: Wired | Linear (1D) barcodes supported: GS1 DataBar Expanded | Optical sensor resolution (W x H): 640 x 480 pixels | 2D (matrix & stacked) barcodes supported: TLC-39 | Pitch reading angle: -65 - 65° | Working distance: 36.8 cm | Linear (1D) barcodes supported: Interleaved 2 of 5 | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 39 | Wavelength: 645 nm | 2D (matrix & stacked) barcodes supported: QR Code | Height: 165 mm | Yaw reading angle: -65 - 65° | Scanner type: 1D/2D | Product colour: Black | 2D (matrix & stacked) barcodes supported: Micro QR Code | Linear (1D) barcodes supported: Code 128 | Motion tolerance (cm/s): 13 | Cables included: Micro-USB | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: EAN-13 | 2D (matrix & stacked) barcodes supported: Composite Codes | Charging base: No | Depth: 99 mm | Weight: 161.6 g | Sensor type: LED | Operating relative humidity (H-H): 5 - 95% | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: Han

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Xin | 2D (matrix & stacked) barcodes supported: Data Matrix | Tilt reading angle: -65 - 65° | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | International Protection (IP) code: IP42 | Standard interfaces: USB, RS-232, RS-485, Keyboard wedge | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | Width: 66 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950