

DeepCool PL800D power supply unit 800 W 20+4 pin ATX ATX Black



Model: R-PL800D-FC0B-EU-V2

Manufacturer: DEEPCOOL

EAN: 6933412721529

Product Code: 610897

R2,140

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Sustainability certificates: ErP | Sustainability certificates: Triman | Sustainability compliance: Yes | Cabling type: Non-Modular | Total power: 800 W | Purpose: PC | SATA power cable length: 650 mm | Fan location: Top | Combined power (+3.3V): 100 W | Compliance certificates: RoHS | Bearing technology: HYB | AC input frequency: 50/60 Hz | Combined power (+5V): 100 W | Input current: 9 - 4.5 A | Max output current (+5V): 20 A | Power protection features: Overheating | Power protection features: Surge protection | SATA power cable length: 450 | Combined power (+5Vsb): 15 W | Power protection features: No load operation | Power protection features: Over voltage | Cooling type: Active | Power Factor Correction (PFC) type: Active | Motherboard power cable length: 55 cm | Power protection features: Surge & inrush protection (SIP) | Power protection features: Over power | Package type: Box | Power protection features: Under voltage | Power protection features: Over current | Width: 150 mm | Combined power (+12V): 648 W | AC input voltage: 100 - 240 V | SATA power cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

length: 550 | PCI Express power connectors (16-pin): 1 | Operating temperature (T-T): 0 - 40 °C | Max output current (+3.3V): 20 A | Height: 86 mm | Max output current (+12V): 54 A | Max output current (-12V): 0.3 A | On/off switch: Yes | Number of SATA power connectors: 6 | Combined power (-12V): 3.6 W | PCI Express power connectors (6+2 pin): 3 | Power supply unit (PSU) form factor: ATX | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Max output current (+5Vsb): 3 A | ATX power connector (20+4 pin): Yes | Depth: 140 mm | Compliance certificates: WEEE | Product colour: Black | Peripheral (Molex) power connectors (4-pin): 2 | Efficiency: 85% | Hold time: 16 ms | Fan diameter: 12 cm | Power Good signal delay range: 100 - 150 ms | Motherboard power connector: 20+4 pin ATX | ATX version: 3.0 | CPU power connector (4+4 pin): Yes | Number of fans: 1 fan(s)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950