



Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s

Model: UDM-Pro-Max

Manufacturer: UBIQUITI

EAN: 810084693254

Product Code: 611559

R14,307

Operating temperature (T-T): -10 - 40 °C | Operating relative humidity (H-H): 5 - 95% | LED indicators: Activity | Ethernet LAN data rates: 1000 Mbit/s | Processor frequency: 2000 MHz | Product colour: Grey | Processor manufacturer: ARM | Reset button: Yes | LED indicators: Ready | LED indicators: Link | Cables included: AC | Ethernet LAN data rates: 10 | Ethernet LAN (RJ-45) ports: 9 | WAN connection: Ethernet (RJ-45), SFP+ | Control display unit: Yes | Ethernet LAN data rates: 2500 Mbit/s | Processor model: Cortex-A57 | Rack capacity: 1U | LED indicators: Error | Quality of Service (QoS) support: Yes | Input voltage: 100 - 240 V | Width: 442.4 mm | Weight: 4.7 kg | Power consumption (max): 60 W | Display type: LCM | Power over Ethernet (PoE): No | Processor family: ARM Cortex | Input current: 2 A | Height: 43.7 mm | SSD capacity: 128 GB | Routing protocols: OSPF | DC input voltage: 12 V | Mounting type: Rack mounting | Depth: 285.6 mm | Routing protocols: BGP | Ethernet LAN data rates: 100 | Internal memory: 8000 MB | Heat dissipation: 205 BTU/h | Multicast

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

support: Yes | Number of processors installed: 1 | DHCP server: Yes | VLAN support: Yes | Firewall security: Yes | Input frequency: 50/60 Hz | Built-in processor: Yes | Flash memory: 32000 MB | Electromagnetic (EMP) protection (air): 15 kV | Electromagnetic (EMP) protection (contact): 8 kV | Electromagnetic (EMP) protection: Yes | SFP+ ports quantity: 2 | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Warnings: Do not use in damp conditions. | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: CE | Port aggregation: Yes | Electrostatic Discharge (ESD) protection (air): 15 kV | Enclosure material: Aluminium/SGCC | Electrostatic Discharge (ESD) protection (contact): 8 kV | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950