



IP Camera DAHUA IPC- HDW1639T-A-IL- 0280B-S6 White



Model: 51752

Manufacturer: DAHUA

EAN: 6923172568779

Product Code: 616578

R2,107

Supported graphics resolutions: 2560 x 1440 | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Power consumption (Power over Ethernet (PoE)): 5.4 W | Video compression formats: H.265+ | Maximum aperture number: 1.6 | Power consumption (typical): 3.6 W | Ethernet LAN (RJ-45) ports: 1 | Video compression formats: M-JPEG | Built-in loudspeaker: Yes | Video compression formats: H.265 | Observe distance (wide): 35.7 m | Video compression formats: H.264+ | Bluetooth: No | Video compression formats: H.264 | Depth: 192.7 mm | RAM capacity: 1024 MB | Mounting type: Wall/ceiling | Connectivity technology: Wired | 4G LTE: No | Networking standards: IEEE 802.1x | Type: IP security camera | Alarm input/output: No | Weight: 340 g | Frame rate: 25 / 30 fps | Picture enhancement: D-WDR, 3D-DNR, ROI, BLC/HLC | Web-based management: Yes | Closest focusing distance: 1.9 m | Networking standards: IEEE 802.3af | Housing material: Metal | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 3072 x 2048 | Width: 70.5 mm | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 2592 x 1944 | People detection : Yes | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Adjustment shutter speed: Auto/Manual | Operating temperature (T-T): -40 - 60 °C | ROM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

capacity: 128 MB | Signal-to-Noise Ratio (SNR): 56 dB | Ethernet interface type: 10 Megabit Ethernet | Ethernet interface type: 100 Megabit Ethernet | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Aperture type: Permanent | DC output voltage: 12V | Number of lenses: 1 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Sensor type: 1/2.7" CMOS | Mobile operating systems supported: Android | Wi-Fi: No | Number of illumination LEDs: 1 | Night vision distance: 30 m | Audio codecs: G.711a / G.711Mu / G.723 / G.726 / PCM | Total megapixels: 8 MP | Camera shutter speed: 1/3 - 1/100000 s | Mobile operating systems supported: iOS | Two-way talk: Yes | Optical sensor size: 25.4 / 1.8 mm (1 / 1.8") | Compatible memory cards: MicroSDXC | Network interface : RJ-45 10/100 | Number of cameras: 1 | International Protection (IP) code: IP67 | Lens viewing angle, vertical: 57° | Height: 66.4 mm | Compatible memory cards: MicroSDHC | Horizontal rotation angle: 0 - 360° | Lens type: Fixed focal length lens | Flip & mirror: Yes | Compatible memory cards: MicroSD (TransFlash) | Web browser: Yes | Progressive scan: Yes | Lens viewing angle, horizontal: 110° | Additional information: Human detection, ONVIF Port: 80, WEB Server: Built-in, Mobile phone access: Port: 37777/through the cloud (P2P) | Video streaming: Yes | Operating relative humidity (H-H): 0 - 95% | Maximum memory card size: 256 GB | (cdm) Menu languages: PL, Eng, FR, DE and others | Number of sensors: 1 | Supported graphics resolutions: 1280 x 720 | Motion detection : Yes | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Vertical rotation angle: 0 - 90° | Form factor: Bullet | Audio RCA outputs: 1 | Additional information: D-WDR - Wide Dynamic Range of illumination 3D-DN | Number of memory card slots: 1 | Noise reduction technology: 3D noise reduction | Power source type: DC, PoE | RCA input: 1 | LED type: IR | Built-in microphone: Yes | Night vision: Yes | Placement supported: External / Internal | Focal length range: 2.8 mm | Number of users: 6 user(s) | Lens: Permanent

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950