

NETGEAR 52- Port PoE Gigabit/10G Stackable Smart Switch (GS752TXP)



Model: GS752TXP-300EUS

Manufacturer: NETGEAR

EAN: 606449171181

Product Code: 620976

R17,358

Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Latency (10 Gbps): 4.107 μ s | Operating temperature (T-T): 0 - 50 °C | Product colour: Black | Power source: AC | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Full duplex: Yes | Flow control support: Yes | Rate limiting: Yes | SSH/SSL support: Yes | Storage temperature (T-T): -20 - 70 °C | Packet buffer memory: 16 MB | 10G support: Yes | Power over Ethernet (PoE): Yes | Storage relative humidity (H-H): 0 - 95% | MAC address filtering: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1ab | Heat dissipation: 2944.6 BTU/h | Switch type: Managed |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Networking standards: IEEE 802.1as | Power supply included: Yes | Operating relative humidity (H-H): 0 - 95% | Operating altitude: 0 - 3000 m | Mean time between failures (MTBF): 1296949 h | Static route: Yes | Weight: 5.54 kg | Power consumption (max): 51 W | Power over Ethernet plus (PoE+) ports quantity: 48 | Height: 43 mm | Networking standards: IEEE 802.3u | Depth: 345 mm | Noise level: 36.6 dB | Port mirroring: Yes | Stackable: Yes | Networking standards: IEEE 802.1x | MAC address table: 16000 entries | Number of static routes: 32 | Non-operating altitude: 0 - 3000 m | Networking standards: IEEE 802.1D | Virtual LAN features: Voice VLAN | DHCP features: DHCP client | Width: 440 mm | Rack mounting: Yes | Built-in processor: Yes | Networking standards: IEEE 802.1w | Flash memory: 64 MB | Switch layer: L2/L3/L4 | Broadcast storm control: Yes | Total Power over Ethernet (PoE) budget: 380 W | Link aggregation: Yes | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | VLAN support: Yes | Spanning tree protocol: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950