



**Ubiquiti UniFi
Pro XG 10 PoE
Managed L2/L3
10G Ethernet
(100/1000/10000)
Power over
Ethernet (PoE)
1U Grey**

Model: USW-Pro-XG-10-PoE

Manufacturer: UBIQUITI

EAN: 810177160137

Product Code: 620979

R16,152

Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Power supply included: Yes | Power connector: AC/DC | Switching capacity: 240 Gbit/s | Jumbo frames support: Yes | Number of VLANs: 1000 | 10G support: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Rate limiting: Yes | Virtual LAN features: Interface-based VLAN | Forwarding rate: 179 Mpps | Multicast support: Yes | Stackable: Yes | Virtual LAN features: Voice VLAN | Throughput: 120 Gbit/s | Loop protection: Yes | Port mirroring: Yes | Static route: Yes | MAC address table: 32000 entries | Packet buffer memory: 2 MB | SFP+ module slots quantity: 2 | Broadcast storm control: Yes | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | DHCP features: DHCP server | Switch type: Managed | DHCP features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

DHCPv6 snooping | Switch layer: L2/L3 | DHCP features: DHCP guarding | Backlight display: Yes | Rack mount kit: Yes | Flow control support: Yes | IGMP snooping: Yes | DHCP features: DHCP relay | IPv4 routes: 12000 | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | 10G Ethernet (copper) ports quantity: 10 | Power over Ethernet 4PPoE (PoE++) ports quantity: 10 | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Federal Communications Commission (FCC) | Display type: LCM | Manual: Yes | Weight: 4.6 kg | Operating relative humidity (H-H): 10 - 90% | Depth: 285 mm | Power consumption (max): 520 W | AC input frequency: 50/60 Hz | Height: 44 mm | LED indicators: System | Cables included: Power | AC input voltage: 100 - 240 V | Power over Ethernet (PoE) power per port: 15.4 W | Form factor: 1U | Reset button: Yes | Total Power over Ethernet (PoE) budget: 400 W | Width: 442.4 mm | Power over Ethernet (PoE): Yes | Power source: AC/DC | Quality of Service (QoS) support: Yes | Operating temperature (T-T): -5 - 40 °C | Product colour: Grey | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Rack mounting: Yes | VLAN support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950