



i-tec Metal USB-C Nano 2x Display Docking Station with PD 100 W + Charger 100W

Model: C31NANOHDM2D100

Manufacturer: I-TEC

EAN: 8595611707155

Product Code: 630044

R2,523

Small metal USB-C docking station capable of supporting up to two external monitors simultaneously*. Simply connect your laptop or tablet (no need to install drivers) and reap the benefits of quick USB data transfer and connection to the internet via a LAN port. And of course, the docking station can also power your laptop with up to 100 W, meaning you will be able to charge all laptops and tablets that support charging via USB-C (USB-C Power Delivery).

Brushed aluminium body grants the docking station sufficient durability and resilience even during frequent travel. The integrated USB-C cable is sufficiently long for comfortable connection even if the USB-C port is located in the upper portion of the screen frame (typical for hybrid laptops/tablets).

The docking station is also fully compatible with tablets and laptops featuring a Thunderbolt 3/4 port.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Connect up to two external monitors.
- Power delivery: up to 100 W
- Fitted with two HDMI ports
- 2x USB 3.2 (5 Gbps), 2x USB 2.0 and 1x USB-C ports will allow you to easily connect your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Supports Windows 10/11, macOS, Android, Chrome OS and Linux

CHARGER

This universal USB-C power adapter with power of 100 W is a great choice for powering any laptop or other device equipped with a USB-C connector that supports USB-C Power Delivery with a maximum power demand of 100 W.

The voltage is set automatically according to the USB Power Delivery specification 2.0 v1.2 in the individual profiles in following steps: 5 V / 9 V / 12 V / 15 V / 19 V / 20 V with max. 5 A current consumption. The power adapter is lightweight and very portable; it is equipped with intelligent current overload, overvoltage, short circuit and overheating protection.

* macOS does not support Multi Stream Transport (MST) technology, meaning that when connected to a device running macOS, both connected external monitors will display the same image.