



Lindy 7.5m Cat.6A S/FTP GRS TPE Cable, Grey



Model: 47922

Manufacturer: LINDY

EAN: 4002888479226

Product Code: 635727

R817

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 Gigabit Ethernet (10GBaseT). The TPE Jacket is a more flexible alternative than PVC cables with a flex rating of 10 million it has high impact and tear resistance making it a very durable jacket material and easy to install. Each cable is packaged in recycled material, supporting a greener planet and reducing our carbon footprint.

This GRS certified ecological patch cord comes from the reuse of recycled raw materials and has received GRS (Global Recycled Standard) certification. With more than 50% of the weight of the patch cord made of recycled materials. The cord sheath and the pair insulation are made with quality recycled materials, these cables fulfil strict GRS certification criteria.

Cat.6A cable, offers enhanced shielding to reduce interference and ensure optimal performance, especially in environments with high electromagnetic interference (EMI). The cable's shielding is achieved using an overall braid as well as a foil shield on each of the twisted pairs (S/FTP). Cat.6A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

cables meet the requirements of 10 Gigabit Ethernet (10GBaseT) with an operating frequency of up to 500MHz. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a recycled polybag utilising 100% GRS certified recycled materials.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m.