



Ubiquiti Pro Max 16 PoE Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Model: USW-Pro-Max-16-PoE

Manufacturer: UBIQUITI

EAN: 810084694572

Product Code: 639736

R9,444

Cables included: Power | Port mirroring: Yes | Networking standards: IEEE 802.1x | Housing material: Steel | Warnings: Avoid contact of the device with liquid. | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE) power per port: 15 W | Throughput: 42 Gbit/s | Switching capacity: 84 Gbit/s | Power connector: DC-in jack | Redundant power supply (RPS) support: Yes | Power over Ethernet plus (PoE+) ports quantity: 12 | Power over Ethernet 4PPoE (PoE++) ports quantity: 4 | Broadcast storm control: Yes | Height: 43.7 mm | Gigabit Ethernet (copper) ports quantity: 12 | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Weight: 2.1 kg | Mounting brackets included: Yes | Warnings: Make sure the ventilation of

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

the equipment is not blocked. | Power consumption (max): 30 W | Basic switching RJ-45 Ethernet ports quantity: 16 | Forwarding rate: 62.496 Mpps | Jumbo frames support: Yes | Manual: Yes | Compliance certificates: CE | AC input frequency: 50/60 Hz | Power source: AC/DC | SFP+ module slots quantity: 2 | Compliance certificates: Industry Canada (IC) | IGMP snooping: Yes | LED indicators: System | Flow control support: Yes | Rate limiting: Yes | Product colour: Grey | Width: 325.1 mm | Power over Ethernet (PoE): Yes | Loop protection: Yes | Multicast support: Yes | Power supply included: Yes | AC input voltage: 100 - 240 V | Depth: 160 mm | 10G support: Yes | Operating relative humidity (H-H): 10 - 90% | Compliance certificates: Federal Communications Commission (FCC) | Virtual LAN features: Voice VLAN | Operating temperature (T-T): -5 - 40 °C | Rack mounting: Yes | Switch type: Managed | Total Power over Ethernet (PoE) budget: 180 W | Reset button: Yes | DHCP features: DHCP snooping | Switch layer: L3 | DHCP features: DHCPv6 relay | Display type: LCM | DC input voltage: 44 - 57 V | 2.5G Ethernet (copper) ports quantity: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950