



Ubiquiti Pro Max 24 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Model: USW-Pro-Max-24

Manufacturer: UBIQUITI

EAN: 810084692738

Product Code: 639756

R10,580

Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Throughput: 56 Gbit/s | Broadcast storm control: Yes | Stackable: Yes | SFP+ module slots quantity: 2 | Static route: Yes | Virtual LAN features: Voice VLAN | Rack mount kit: Yes | Flow control support: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Rate limiting: Yes | Sustainability certificates: CE | Sustainability certificates: Federal Communications Commission (FCC) | Port mirroring: Yes | Loop protection: Yes | 2.5G Ethernet (copper) ports quantity: 8 | Switch layer: L3 | LED indicators: Speed | Power supply included: Yes | 10G support: Yes | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Status | DHCP features: DHCP snooping | Form factor: 1U | VLAN support: Yes | DHCP features: DHCP relay | Reset button: Yes | Product colour: Grey | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

switching RJ-45 Ethernet ports quantity: 24 | Power consumption (max): 50 W | LED indicators:
Network | Depth: 325 mm | Switching capacity: 112 Gbit/s | Power source: AC/DC | Height: 43.7 mm |
Cables included: Power | Width: 442.4 mm | Weight: 4.3 kg | Rack mounting: Yes | Operating relative
humidity (H-H): 10 - 90% | IGMP snooping: Yes | Power over Ethernet (PoE): No | AC input frequency:
50/60 Hz | Networking standards: IEEE 802.1x | Basic switching RJ-45 Ethernet ports type: 2.5G
Ethernet (100/1000/2500) | Operating temperature (T-T): -5 - 40 °C | Power connector: AC/DC |
Jumbo frames support: Yes | Display type: LCM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950