



ENDORFY Vero L6 power supply unit 650 W 24- pin ATX ATX Black



Model: EY7A015

Manufacturer: ENDORFY

EAN: 5903018668918

Product Code: 648586

R1,952

Doesn't contain: Lead | PCI Express power connectors (16-pin): 1 | Warranty period: 5 year(s) | Doesn't contain: Cadmium | Doesn't contain: Mercury | Number of SATA power connectors: 5 | Max output current (+5V): 20 A | Max output current (+5Vsb): 3 A | EPS power connector (4+4 pin): Yes | Motherboard power connector: 24-pin ATX | Peripheral (Molex) power cable length: 800 mm | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | Peripheral (Molex) power connectors (4-pin): 1 | Package height: 100 mm | On/off switch: Yes | Height: 87 mm | Depth: 140 mm | Cables included: AC | Width: 150 mm | Manual: Yes | AC input frequency: 50 Hz | Product colour: Black | Package weight: 2.09 kg | Package width: 273 mm | Cooling type: Active | Package depth: 220 mm | Input current: 5 A | 80 PLUS certification: 80 PLUS Bronze | Weight: 1.57 kg | Power supply unit (PSU) form factor: ATX | Illumination: No | Power Factor Correction (PFC) type: Active | Combined power (+12V): 648 W | Combined power (+3.3V): 100 W | AC input voltage: 200 - 240 V | Mean time between failures (MTBF): 80000 h | ATX Power connector (24-pin): Yes | SATA power cable length:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

800 mm | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Over power | SATA power cable length: 500 | Motherboard power cable length: 57 cm | Max output current (+12V): 54 A | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Surge & inrush protection (SIP) | Power protection features: Overheating | Bearing technology: FDB | Purpose: PC | PCI Express power connectors (6+2 pin): 2 | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | Combined power (+5Vsb): 15 W | Cabling type: Non-Modular | Total power: 650 W | Number of fans: 1 fan(s) | ATX version: 3.1 | Fan diameter: 12 cm | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CCC | Compliance certificates: UKCA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950