



IP CAMERA

DAHUA IPC-HFW2849S-S-IL-0280B

Model: IPC-HFW2849S-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581570

Product Code: 649895

R3,411

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-02-22 | Number of lenses: 1 | Lens type: Fixed focal length lens | Lens viewing angle, diagonal: 132° | Lens viewing angle, horizontal: 111° | Lens viewing angle, vertical: 58° | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Warnings: The product contains electronic components do not dispose of with the normal household waste. | DC output voltage: 12 | Number of cameras: 1 | Connectivity technology: Wired | International Protection (IP) code: IP67 | White balance: Outdoor | Closest focusing distance: 1.5 m | White balance: Manual | Networking standards: IEEE 802.3af | Noise reduction: Yes | Web browser: Yes | Ethernet interface type: Fast Ethernet | Operating relative humidity (H-H): 0 - 95% | Focal length range: 2.8 mm | Number of users: 20 user(s) | Maximum resolution: 3840 x 2160 pixels | Adjustment shutter speed: Auto/Manual | Progressive scan: Yes | Housing material: Metal | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | White balance: Street lamp | Back Light Compensation (BLC): Yes | White balance:

Natural | Type: IP security camera | White balance: Auto | Web-based management: Yes | Video

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

compression formats: H.264B | Depth: 166.2 mm | Video motion detection: Yes | Weight: 470 g |
Video compression formats: H.265 | LED type: IR / White light LED | Wi-Fi: No | Form factor:
Tube/dome | Audio formats supported: G.711Mu | Audio formats supported: G.726 | Tilt angle range:
0 - 90° | Power consumption (max): 5 W | Video compression formats: M-JPEG | Audio formats
supported: G.711a | Sensor type: CMOS | Ethernet LAN: Yes | Audio formats supported: PCM | Built-in
HDD: No | Maximum aperture number: 1.6 | Video compression formats: H.264+ | Pan range: 0 -
360° | Video compression formats: H.265+ | Video compression formats: H.264 | Bluetooth: No |
Video compression formats: H.264H | Supported graphics resolutions: 2048 x 1536 (QXGA) |
Supported graphics resolutions: 3072 x 1728 | Supported graphics resolutions: 3072 x 2048 |
Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 704 x 576 |
Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1280 x 720 |
Supported graphics resolutions: 2880 x 1620 | Number of sensors: 1 | Supported graphics
resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Mobile operating systems
supported: iOS | Supported graphics resolutions: 1920 x 1080 | Mobile operating systems supported:
Android | ROM capacity: 128 MB | Supported graphics resolutions: 352 x 288 | Supported graphics
resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Width: 70 mm | Frame rate:
30 fps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Total megapixels: 8 MP |
Height: 70 mm | Number of illumination LEDs: 2 | Power consumption (typical): 2.7 W | Gain control
type: Auto/Manual | Internal memory: 256 MB | Quality of Service (QoS) support: Yes | Product
colour: White | Power consumption (Power over Ethernet (PoE)): 5.9 W | Highlight Compensation
(HLC): Yes | Night vision distance: 30 m | Wide Dynamic Range (WDR): 120 dB | Video streaming: Yes
| Region of Interest (ROI) encoding: Yes | Mounting type: Ceiling/wall | Storage temperature (T-T): -40
- 55 °C | Camera shutter speed: 1/3 - 1/100000 s | Noise reduction technology: 3D noise reduction |
Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Placement supported: External / Internal | Power source
type: DC, PoE | Operating temperature (T-T): -40 - 55 °C | Minimum illumination: 0.008 lx | Night
vision: Yes | Built-in microphone: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950