

TP-LINK 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: Archer MR600

Manufacturer: TP-LINK

EAN: 6935364089832

Product Code: 650183

R3,274

Receiver sensitivity: 5 GHz: 11a 54M: -74 dBm 11ac HT20: -66 dBm 11ac HT40: -63 dBm 11ac HT80 : -59 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm 2.4 GHz: 11g 54M: -74 dBm 11n HT20: -72 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, IPSec VPN , OpenVPN | Certification: CE, RoHS | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 Mbit/s | Package width: 307 mm | AC adapter included: Yes | Product colour: Black | Quick installation guide: Yes | Filtering: Yes | Reset button: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11a | Package height: 70 mm | Networking standards: IEEE 802.11b | Security algorithms: WPA | Package type: Box | Networking standards: IEEE 802.11ac | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Security algorithms: 128-bit WEP | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 867 Mbit/s | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Ethernet LAN interface type: Gigabit Ethernet | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 223 mm | Networking standards: IEEE 802.11a | Security algorithms: 64-bit WEP | Security

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

algorithms: WPA2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | 3G: Yes | Antennas quantity: 2 | Wi-Fi standards: 802.11b | DHCP client: Yes | Ethernet WAN: Yes | Ethernet LAN (RJ-45) ports: 4 | Stateful Packet Inspection (SPI): Yes | DC-in jack: Yes | Cables included: LAN (RJ-45) | 4G: Yes | Output voltage: 12 V | Windows operating systems supported: Yes | Operating temperature (T-T): 0 - 40 °C | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 1000 Mbit/s | Mac operating systems supported: Yes | Width: 229 mm | LED indicators: LAN, Power, WLAN | AC input voltage: 100 - 240 V | Power source type: AC, DC | Warnings: Do not expose the device to water or moisture. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Ethernet LAN: Yes | Depth: 160 mm | Harmonized System (HS) code: 85176990 | 4G bands supported: 1800 | SIM card slot: Yes | Guest access: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | Output current: 1.5 A | Dual SIM support: No | Detachable antenna(s): Yes | 4G bands supported: 900 | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Universal Plug and Play (UPnP): Yes | USB port: No | Supported network protocols: IPv4, IPv6 | Firewall: Yes | SIM card type: MicroSIM | 4G standard: LTE | Parental control: Yes | 4G bands supported: 700 | 4G bands supported: 2300 | WLAN data transfer rate (second band): 300 Mbit/s | Port forwarding: Yes | Wall mountable: No | 3G standards: HSPA | Port triggering: Yes | WLAN data transfer rate (first band): 867 Mbit/s | DMZ support: Yes | Height: 37 mm | Routing protocols: IP | WPS push button: Yes | Mobile network generation: 4G | Firewall security: Domain Filter, IP, MAC Address Binding | Number of products included: 1 pc(s) | DSL WAN: No | Product type: Tabletop router | DHCP server: Yes | Dynamic DNS (DDNS): Yes | WAN connection type: RJ-45 | DoS attack prevention: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 3G standards: UMTS | 3G bands supported: 850 | URL filtering: Yes | 3G bands supported: 900 | 5G: No | 3G bands supported: 2100 MHz | 3G/4G USB modem compatibility: No | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | Memory card slot(s): No | Number of guest networks (5 GHz): 1 | Number of guest networks (2.4 GHz): 1 | Antenna design: External

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950