



Axagon HMC-5 USB 3.2 Gen 1 hub, 2x USB-A, HDMI, SD/microSD, PD 100W, 20cm USB-C cable

Model: HMC-5

Manufacturer: AXAGON

EAN: 8595247906175

Product Code: 652429

R1,438

Multiport USB-C 3.2 Gen 1 hub AXAGON HMC-5 expands your laptop, computer or phone with four ports and SD / microSD card reader. You can easily and quickly connect up to two USB devices, card reader and HDMI display to your computer at the same time via the double-sided USB-C connector. You also get the possibility to supply laptop using Power Delivery technology at the same time. The USB-C hub will provide you with a simple and compact 5in1 docking station for notebook like MacBook Pro.

The USB hub offers two USB outputs with standard USB-A connectors. The hub can also handle permanent connection of several external drives simultaneously. Transfer rate up to 5Gb/s thanks to

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

the fast USB 3.2 Gen 1 interface. The hub will also charge phones and tablets with a current up to 1.5A/5V. So hub can easily charge an Android smartphone, Apple iPhone, Apple iPad etc.

USB-C connector is dedicated to power up a laptop or mobile phone using Power Delivery 3.0 technology by power up to 100W. Connect the USB-C Power Delivery charger to the hub and connect the hub to the laptop. This saves one USB-C port. The condition is a laptop with Power Delivery charging support from the USB-C port and a suitable PD charger.

HDMI output provides high quality image up to 4K/30Hz Ultra HD resolution and supports multi-channel audio transmission. Popular gaming resolution WQHD 2560 x 1440px at 60Hz or FullHD 1920 x 1080px at 60, 100 and 120Hz max. are also supported. DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output.

Card reader supports all current versions of SD and microSD cards including SDXC and microSDXC with capacity up to 2TB. High data transfer speed ensured by USB 3.2 Gen 1 interface. The card reader enables simultaneous handling of cards in both slots and direct copying between them.

Elegant aluminum body ensures mechanical resistance and quality cooling. The finely structured surface with no fingerprint remains will also please you.

Port replicator is an ideal accessory for laptops without USB-A connectors, card reader and video output. You can use your current USB peripherals without having to purchase new ones. Thanks to the Plug and Play and Hot Plug functions, the connection of the hub is very simple without complicated installation. It is also possible to easily connect and disconnect peripherals while the computer is running. The hub does not afraid of connection to phones with a USB-C connector - for example, you can connect a flash drive, keyboard, mouse, display, TV or projector to the phone.

Input:

- 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-C male connector.
- Backward compatible with USB 3.1 Gen 1 / USB 3.0 a USB 2.0.
- Compatible with Thunderbolt 3.
- Input USB type C male connector on fixed 20 cm cable.

USB outputs:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 2x SuperSpeed USB port, USB-A female connector.
- 1x USB type C Power Delivery port (only charging), USB-C female connector.
- Supports transmission rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
- The total bandwidth / transmission rate of the box is determined by the USB 3.2 Gen 1 interface used (theoretically up to 5 Gbit/s).
- USB-C hub can handle connection of several external drives simultaneously.
- Charging mobile devices (including iPad) with current up to 1.5A in each of the hub ports. The total charging current (which is divided into ports) reaches up to 2.5A at 5V (depending on the capabilities of the computer's USB port).

HDMI output:

- HDMI.
- HDMI A (F) female connector.
- Maximum supported resolution 4K / 4096 x 2160 at 30 Hz.
- WQHD resolution 2560 x 1440 at 60 Hz max.
- FullHD resolution 1920 x 1080 at 60, 100, 120 Hz max.
- DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output. Correct OS is also necessary. The video output function will not be available without these requirements.
- HPD (Hot-Plug-Detect) support.
- TMDS (Transition Minimized Differential Signaling) support.
- Full HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) support.
- Up to 8-channel LPCM audio, compressed audio (AC-3, DTC) and HBR audio format support.
- Sample rate up to 192 kHz and 24bit audio support – depends on source and target device i.e. notebook/phone and TV/display/AV receiver.

The card reader - two slots:

- Micro SD slot: microSD / microSDHC / microSDXC / TransFlash,
- SD slot: SecureDigital / SDHC / SDXC, MultiMedia Card, MMC 4.0, MMC Dual Voltage, MMC mobile, RS-MMC, with adapter miniSD, microSD / microSDHC / microSDXC, MMC Micro.

The reader supports the following flash card specifications:

- SD 1.0/1.1 (SD - Secure Digital, up to 2 GB).
- SD 2.0 (SDHC - Secure Digital High Capacity, up to 32 GB).

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- SD 3.0 (SDXC - Secure Digital eXtended Capacity, up to 2 TB).
- MMC and eMMC 3.x/4.0/4.1/4.2/4.3/4.4/4.5/5.0 (8-bit).
- Supports SD 3.01 and SD Jukebox applications (CPRM features).
- Supports Ultra High Speed bus UHS-I (SDR12/SDR25/SDR50/DDR50/SDR104) speed up to 104 MB/s.
- Supports hardware ECC (Error Correction Code) and CRC (Cyclic Redundancy Check) features.
- 2 LUN - in file managers, the reader is indicated as two disk drive.

Power Delivery:

- Power Delivery 3.0 support – device power supply from the PD wall charger via USB-C hub.
- Maximum power supply power via PD USB-C hub output 100W - 20V/5A.
- Notebook or phone with Power Delivery charging support from the USB-C port and a suitable PD charger is necessary.

Other features:

- Possibility to connect your device while running thanks to the Hot Plug support.
- Full Plug and Play support.
- Standby mode support.
- Power via USB bus - USB bus power or from PD wall charger.
- Heavy-duty aluminium body for better hub cooling. Higher surface hub temperature is not a problem - the heat generated by the hub operation is better dissipated and transferred to the surroundings.
- White LED indicates computer USB port connection (steady light).
- High quality shielded cable ensures fast communication speed and minimal unwanted interference.
- Dimensions 110 x 35 x 12.5 mm.
- Weight 55 g (incl. cable).
- USB cable length 20 cm.

Supported operating systems:

- Microsoft Windows 10, 11, Mac OS, Linux, Android and Chrome OS.

Compatibility depends on used OS and support from device manufacturer.

- Note 1: Drivers are included with supported operating systems and are installed automatically. No other drivers need to be installed.

- Note 2: DisplayPort Alternate Mode (DP Alt Mode) is only supported in updated OS and also
- The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

depends on support from device (notebook, phone) manufacturer.

Package contains:

- USB-C hub with fixed 20 cm long cable,
- printed installation guide in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box with a hanging hole.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950