



GIGABYTE P550SS power supply unit 550 W 20+4 pin ATX ATX Black



Model: GP-P550SS

Manufacturer: GIGABYTE

EAN: 4719331554187

Product Code: 662503

R1,425

Number of SATA power connectors: 5 | Max output current (+5Vsb): 3 A | CPU power cable length: 60 cm | ATX power connector (20+4 pin): Yes | CPU power connector (4+4 pin): Yes | Floppy drive power connector: 1 | Peripheral (Molex) power cable length: 500 mm | PCI Express connector: Yes | Max output current (-12V): 0.3 A | PCI Express power cable length: 50 cm | Motherboard power connector: 20+4 pin ATX | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 2 | Total power: 550 W | Width: 150 mm | Product colour: Black | Power supply unit (PSU) form factor: ATX | Floppy disk drive connector: Yes | Fan location: Top | Cabling type: Non-Modular | Depth: 140 mm | Efficiency: 90% | Power factor: 0.9 | Harmonized System (HS) code: 84733020 | Cooling type: Active | ATX version: 3.0 | Bearing technology: HDB | Number of fans: 1 fan(s) | Height: 86 mm | Purpose: PC | Fan diameter: 12 cm | Motherboard power cable length: 60 cm | Combined power (+3.3V): 100 W | AC input frequency: 50/60 Hz | On/off switch: Yes | Input current: 6.3 A | SATA power cable length: 500 | 80 PLUS certification: 80 PLUS Bronze | Mean time between

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

failures (MTBF): 100000 h | Hold time: 16 ms | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | Max output current (+12V): 45.8 A | Combined power (+12V): 549.6 W | Power Factor Correction (PFC) type: Active | AC input voltage: 155-240 V | Combined power (-12V): 3.6 W | Combined power (+5V): 200 W | Max output current (+3.3V): 20 A | Max output current (+5V): 20 A | Power protection features: Overheating | Combined power (+5Vsb): 15 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950