



Power Supply GIGABYTE GP- P550SS ICE ATX PC 155-240 V 550 W GP- P550SSICE

Model: GP-P550SS ICE

Manufacturer: GIGABYTE

EAN: 4719331554910

Product Code: 662616

R1,468

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

- Ice white aesthetics
- 80 PLUS Silver certified (230V EU)
- Support Intel ATX 3.0 standard (compatible with ATX 3.1)
- 120mm Fluid Dynamic Bearing (FDB) Fan
- Flat cable design

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Powerful single +12V rail
- OVP/OPP/SCP/UVPP/OCP/OTP protection

Summary: GIGABYTE P550SS ICE Power Supply - PCIe 5.0, 80 PLUS Silver, 120mm Fan, ATX 3.0 compatible, EU Plug. Total power: 550 W, AC input voltage: 155-240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Silver. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Width: 140 mm, Depth: 150 mm, Height: 86 mm | Vendor Homepage: <https://www.gigabyte.com/Power-Supply/GP-P550SS-ICE> | AC input frequency: 50/60 | AC input voltage: 155-240 | Combined power (+12V): 549.6 | Combined power (+3.3V): 100 | Combined power (+5V): 100 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 90 | Hold time: 16 | Input current: 6.3 | Max output current (+12V): 45.8 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Power Factor Correction (PFC) type: Active | Power Good signal delay range: 100 - 150 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 550 | ATX power connector (20+4 pin): Yes | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 2 | Motherboard power cable length: 600 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 5 | PCI Express connector: Yes | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 4 | 80 PLUS certification: 80 PLUS Silver | ATX version: 3.1 | Bearing technology: Ball bearing | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan location: Top | Number of fans: 1 | On/off switch: Yes | Product colour: White | Depth: 150 | Height: 86 | Weight: 1950 | Width: 140 | Package depth: 206 | Package height: 117 | Package type: Box | Package weight: 2110 | Package width: 254 | Warranty period: 3 | Model name: GP-P550SS ICE | Units per Shipping Box: 5 | Unit Calculated Volume: 0.007502 | Unit Calculated Weight: 2.19

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950