



DeepCool CL6600 Midi Tower Black



Model: R-CL6600-BKNNA0-G-1

Manufacturer: DEEPCOOL

EAN: 6933412765295

Product Code: 662884

R4,427

Depth: 457.5 mm | Suitable for: Gaming | Power supply included: No | Bearing type: Fluid bearing | Number of 3.5" bays: 3 | Width: 235 mm | Type: PC | Material: Acrylonitrile butadiene styrene (ABS) | Weight: 11.8 kg | Material: Tempered glass | Material: SPCC | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Height: 533.5 mm | Combo headphone/mic port: Yes | Form factor: Midi Tower | Product colour: Black | Reset button: Yes | Number of rear fans supported (max): 1 | Power supply location: Bottom | Number of 2.5" bays: 2 | Illumination colour: Multi | Number of expansion slots: 7 | Supported power supply form factors: PS2 | Liquid cooling capability: Yes | Supported power supply form factors: SFX | Supported power supply form factors: SFX-L | Bottom fans installed: 2x 120 mm | Maximum CPU cooler height: 17.5 cm | Pump load current: 0.29 A | Supported HDD sizes: 2.5" | Supported HDD sizes: 3.5" | Top fans diameters supported: 120 | Rear radiator sizes supported: 120 | Fan connector: 4-pin | Supported power supply form factors: ATX | Fan rated voltage: 12 V | Top fans diameters supported: 140 mm | Pump connector: 4-pin | Side window: Yes | Cable management: Yes | Illumination: Yes | Pump motor speed: 2500 RPM | Radiator height: 40.2 cm | Fan power consumption: 3.6 W | Supported

motherboard form factors: ATX | Illumination location: Case fans | Maximum graphics card length:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

41.3 cm | Number of bottom fans supported (max): 2 | Front fans diameters supported: 140 mm | Supported motherboard form factors: micro ATX | Supported motherboard form factors: Mini-ITX | Fan rated current: 0.3 A | Number of internal 3.5" bays: 2 | Number of front fans supported (max): 2 | Maximum PSU length: 16 cm | Bottom fans diameters supported: 120 mm | Tempered glass panel(s): Yes | Radiator width: 12 cm | Pump depth: 8 cm | Top radiator sizes supported: 240 | Pump height: 7.6 cm | Number of top fans supported (max): 3 | Top radiator sizes supported: 120 | Top radiator sizes supported: 280 | On/off button: Yes | Rear fans diameters supported: 140 mm | Pump power consumption: 3.48 W | Pump width: 11.8 cm | Top radiator sizes supported: 360 mm | Liquid cooling installed: Yes | Radiator depth: 2.7 cm | Rear fans diameters supported: 120

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950