



Zebra DS2278 Handheld bar code reader 1D/2D LED Black



Model: DS2278-SR7U2100PRW

Manufacturer: ZEBRA

EAN:

Product Code: 667837

R4,637

Certification: EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 | Bluetooth version: 4.0 | Operating temperature (T-T): 0 - 50 °C | Number of batteries supported: 1 | Standard interfaces: Bluetooth, USB | Sustainability certificates: RoHS | Motion tolerance (cm/s): 13 | Depth: 90 mm | Sensor type: LED | Optical sensor resolution (W x H): 640 x 480 pixels | Power source type: Battery | Bluetooth Low Energy (BLE): Yes | Operating relative humidity (H-H): 5 - 95% | Wavelength: 645 nm | Scanner type: 1D/2D | Power source type: DC | Battery life: 84 h | 2D (matrix & stacked) barcodes supported: PDF417 | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported: Composite Codes | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: QR Code | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: Han Xin | Built-in display: No | 2D (matrix & stacked) barcodes supported: MaxiCode | Input voltage: 4.5 - 5.5 V | Width: 66 mm | 2D (matrix & stacked) barcodes supported: Micro QR Code | Weight: 214 g | Storage temperature (T-T): -40 - 70 °C | Charging base: Yes | International Protection (IP) code: IP42 | Product colour: Black | Tilt reading angle: -65 - 65° | Linear (1D) barcodes supported: Code 11 | Linear (1D)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

barcodes supported: EAN-13 | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: Plessey | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: Codabar | LED indicators: Yes | Pitch reading angle: -65 - 65° | Working distance: 36.8 cm | Battery capacity: 2400 mAh | Height: 175 mm | 2D (matrix & stacked) barcodes supported: Aztec Code | Battery technology: Lithium-Ion (Li-Ion) | Linear (1D) barcodes supported: Interleaved 2 of 5 | Connectivity technology: Wired & Wireless

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950