



Axagon PCEA-S2N PCIe - 2x serial port 250 kbps adapter w. SP & LP

Model: PCEA-S2N

Manufacturer: AXAGON

EAN: 8595247905406

Product Code: 673973

R1,131

The AXAGON PCEA-S2N PCI-Express card extends your desktop PC by two RS-232 serial ports with DB-9 connectors.

High performance, seamless compatibility and wide port options are ensured by proven ASIX chipset.

Included low profile brackets allow controller installation into standard and also low profile PC cases.

Input:

- PCI-Express 2.0 interface compatible with PCI-Express 1.0a / 1.1 / 2.1 / 3.0.
- Number of lines 1-Lane (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
- The bandwidth of 1-Lane PCI-Express 2.0 bus 5 Gb/s.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Output:

- 2x serial RS-232 port with DB9 male connectors, the ports are placed on the card's bracket.
- Guaranteed data flow of used RS232 drivers up to 250 kBd.
- Compatible with 16C550 / Extended 16C550 / 16C950 UART.

Other features:

- Plug and Play Support - automatic selection of IRQ and I/O address.
- 256-Byte transmit & receive FIFO buffer for each port.
- Serial port baud rate setting.
- Adjustable word length 5, 6, 7, 8 or 9 bits.
- Adjustable parity (even, odd, none, mark, space), 1, 1.5 or 2 stop bits.
- Adjustable flow control Xon/Xoff, hardware or none.
- The COM port number change.
- Advanced 9-bit data transfer settings and custom baud rate settings.
- Supports TXD, RXD, RTS, CTS, DTR, DCD, DSR, and RI serial signals.
- Serial port electrostatic discharge (ESD) protection exceeding $\pm 15\text{KV}$ Air Gap Discharge and $\pm 8\text{KV}$ Contact Discharge.
- Supports connecting serial devices such as ATMs, cash registers, barcode readers, CNC machines, tablets, modems, POSs or PDAs.
- The ASIX AX99100 chipset is used.

Supported operating systems:

- MS Windows XP / Vista / 7 / 8 / 8.1 / 10 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported all 32 and 64-bit Windows OS versions), with kernel 2.6.11 and above.

Package contains:

- PCI-Express card with a standard bracket,
- low profile brackets,
- multilingual guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
- packed in a cardboard box.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950