



Axagon RVD-HI DisplayPort -> HDMI adapter FullHD



Model: RVD-HI

Manufacturer: AXAGON

EAN: 8595247902740

Product Code: 678713

R889

DisplayPort -> HDMI active adapter AXAGON RVD-HI to connect HDMI monitor/TV/projector to the computer with the DisplayPort output.

The hardware converter without the need for any installation or setup ensures high-quality transfer of image and sound up to 1920x1200 at 60Hz.

The reduction is only one-way, i.e. the converter from DisplayPort to HDMI, not vice versa.

Input:

- DisplayPort v1.1,
- DP connector with latch (M) male,
- connector latch control button.

Output:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- HDMI v1.3a,
- HDMI A (F) female connector.

Supported resolutions:

- max. 1920 x 1200 (16:10) @60Hz WUXGA
- 1920 x 1080 (16:9) Full HD/1080p
- 1680 x 1050 (16:10) WSXGA+
- 1600 x 1200 (4:3) UXGA
- 1600 x 900 (16:9) HD+
- 1440 x 900 (16:10) WXGA+
- 1400 x 1050 (4:3) SXGA+
- 1366 x 768 (16:9) WXGA
- 1360 x 768
- 1280 x 1024 (5:4) SXGA
- 1280 x 960 (4:3) SXGA-
- 1280 x 800 (16:10) WXGA
- 1280 x 768 (5:3) WXGA
- 1280 x 720 (16:9) HD/WXGA/720p
- 1280 x 600
- 1152 x 864 (4:3) XGA+
- 1024 x 768 (4:3) XGA
- 800 x 600 (4:3) SVGA

Other features:

- Sound transfer support.
- DDC (Display Data Channel) support - Intelligent setting of resolution, frequency and other parameters according to the source graphics chip.
- Supported modes: mirroring the primary monitor area (default setting), expanding the primary monitor area.
- HPD (Hot-Plug-Detect) support - communication sequence controlling the connection/disconnection of the device while running.
- Supports power saving modes with spinning down controlled by a source device (PC) and a viewing device (monitor/TV).

- **Power supply via bus - no external power is needed.**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Gold-plated connectors for perfect contact and oxidation limitation.
- NXP PTN3361BBS chip is used.
- Miniature dimensions 56 x 24 x 12 mm.
- Weight only 12 g.
- Working temperature: 0 ~ 40°C.
- Storage temperature: -10 ~ +85°C.

Supported OSs:

- All versions of MS Windows, Mac OS, Linux and other operating systems.
- It is a pure hardware converter, the transfer is provided only by a chip of the adapter without computer participation, no drivers are installed, so the compatibility is not dependent on the operating system used.

Package contains:

- DisplayPort > HDMI converter,
- packed in a cardboard box.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950