



Axagon RVDM-HI14C2 Mini DisplayPort -> HDMI 1.4 cable 1.8m, 4K/30Hz



Model: RVDM-HI14C2

Manufacturer: AXAGON

EAN: 8595247906090

Product Code: 678716

R993

Mini DisplayPort -> HDMI active cable - adapter AXAGON RVDM-HI14C2 to connect HDMI monitor/TV/projector to the computer with the Mini DisplayPort output.

The smart hardware converter without the need for any installation or setup ensures high-quality transfer of image and sound with a resolution up to 4K/30Hz.

Video and audio transfer from a computer or laptop will now be easy. Compact dimensions ensures easy use even in insufficient space. It is an ideal solution - you don't need a HDMI cable and converter. With this active cable everything is integrated into one compact unit.

The cable is only one-way, i.e. Mini DisplayPort to HDMI, not otherwise.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Input:

- Mini DisplayPort v1.2
- Mini DP male connector (M)

Output:

- HDMI v1.4b
- HDMI A (M) male connector

Supported resolutions:

Resolution and frequency depend on monitor and graphics adapter.

- max. 4096 x 2160 (19:10) @30Hz DCI 4K
- 3840 x 2160 (16:9) @30Hz UHD-1 4K (UHDTV)
- 3840 x 1600 (21:9) UW 4K (Ultrawide 1600p)
- 3840 x 1200 (32:10) 29:9 4K (Super ultrawide 1200p)
- 3840 x 1080 (32:9) 32:9 4K (Super ultrawide 1080p)
- 3440 x 1440 (21:9) UWQHD (Ultrawide 1440p)
- 2560 x 2048 (5:4) QSXGA
- 2560 x 1920 (4:3)
- 2560 x 1600 (16:10) WQXGA
- 2560 x 1440 (16:9) @60Hz WQHD
- 2560 x 1080 (21:9) UWFHD (Ultrawide 1080p)
- 2048 x 1536 (4:3) QXGA
- 2048 x 1152 (16:9) QWXGA
- 1920 x 1440 (4:3)
- 1920 x 1200 (16:10) WUXGA
- 1920 x 1080 (16:9) @60, 75, 100 a 120Hz Full HD/1080p
- 1856 x 1392 (4:3)
- 1792 x 1344 (4:3)
- 1680 x 1050 (16:10) WSXGA+
- 1600 x 1200 (4:3) UXGA
- 1600 x 900 (16:9) HD+
- 1536 x 864 (16:9)
- 1440 x 900 (16:10) WXGA+

- 1400 x 1050 (4:3) SXGA+

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 1366 x 768 (16:9) HD
- 1360 x 768 (16:9) HD
- 1280 x 1024 (5:4) SXGA
- 1280 x 960 (4:3) SXGA-
- 1280 x 800 (16:10) WXGA
- 1280 x 768 (5:3) WXGA
- 1280 x 720 (16:9) HD/WXGA/720p
- 1280 x 600
- 1152 x 864 (4:3) XGA+
- 1024 x 768 (4:3) XGA
- 800 x 600 (4:3) SVGA

Other features:

- sound transfer support
- DDC (Display Data Channel) support - Intelligent setting of resolution, frequency and other parameters according to the source graphics chip
- supported modes: mirroring the primary monitor area (default setting), expanding the primary monitor area
- HPD (Hot-Plug-Detect) support - communication sequence controlling the connection/disconnection of the device while running,
- HDCP 1.4 and 2.2
- support of power saving modes with spinning down controlled by a source device (PC) and a viewing device (monitor/TV)
- power supply via bus - no external power is needed
- gold-plated connectors for perfect contact and oxidation limitation
- adapter dimensions 45 x 21 x 12 mm
- total cable length incl. connector 1.8 m
- weight only 62 g

Supported operating systems:

- All versions of MS Windows, Mac OS X, Linux and other operating systems.
- It is a pure hardware converter, the transfer is provided only by the cable chip without computer participation, no drivers are installed, so the compatibility is not dependent on the operating system used.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Package contains:

- Mini DisplayPort > HDMI cable length 1.8 m,
- printed installation manual in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
- packed in a cardboard box.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950