



Microconnect TB4015 Thunderbolt cable 1.5 m 40 Gbit/s Black

Model: TB4015

Manufacturer: MICRO CONNECT

EAN: 5715063003053

Product Code: 688360

R1,701

See the full Premium Assortment at the following link:

<https://www.eetgroup.com/en-zz/campaigns/microconnect-premium>

The Thunderbolt 4 cable data transfer speed is up to 40Gbps ; Please NOTE that the data transfer speed will still depend on what port you are using with. USB 3.1 Gen 2(10 Gbps) USB3.1 gen 1/ 3.0(5 Gbps)← ←

Thunderbolt 4 cable can be 240 Watts of power delivery for rapid charging; Compatible with all Thunderbolt 3+4 & USB C gadget like Ethernet adapter, USB hub, Docking Station,eGPU, PCI-E, Razer Core and Windows DELL XPS15,Alienware17r4, LenovoThinkPad, Pixelbook, Macbook pro15/17/18, etc (Note: Regular Type-C port is NOT compatible)← ←

The Thunderbolt 4 Built in Intel's Thunderbolt chipset . It went through quality checks to ensure durability, reliability and safety; It's safe and ensures consistent performance with your Thunderbolt

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

enabled device.← ←

The Thunderbolt 4 Cable Support dual 4K 60Hz video or one single 8k@60Hz with a single cable when connecting Thunderbolt port; Enjoy ULTRA HD video resolution! Please NOTE that if you are connecting with USB C port to output video; Please make sure your USB C port supports DisplayPort Alternate Mode (Alt Mode) This set up can only produce one 4K display.← ←

The Thunderbolt 4 Cable is made of high quality Coaxial Cable with flexible and flex-resistant TEFLON insulation material and ultra-fine tinned copper are woven; To reduce radiated interference and extend service life, flexible TPE cable jackets for home and industry requirement.