

NEEWER QZ-C Flash Trigger



Model: 10106168

Manufacturer: NEEWER

EAN: 6921268817329

Product Code: 710215

R2,791

NEEWER QZ-C Flash Trigger

The NEEWER QZ-C is an advanced wireless TTL flash trigger that provides full control over lighting in the studio and during outdoor shoots. It supports TTL, manual, and stroboscopic modes, offers fast HSS synchronization up to 1/8000 s, and allows you to control up to five groups of flashes within a range of 100 meters. A color HD OLED touchscreen, a built-in 1000 mAh battery, and a compact design measuring 64 × 41 × 38 mm make it a convenient and highly functional tool for demanding photographers.

Intuitive operation just like on a smartphone

The color HD OLED touchscreen allows you to quickly change settings with taps and swipes. Adjustable display brightness ensures good visibility both in the studio and in direct sunlight, while the screen lock feature prevents accidental changes to settings during operation. Additionally, physical buttons and a multifunction dial allow for convenient control even while wearing gloves.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

TTL, HSS, and TCM for faster operation

The trigger supports automatic TTL metering, manual power adjustment from 1/128 to 1/1, and stroboscopic flash. HSS synchronization up to 1/8000 s allows you to shoot with a wide-open aperture even in intense daylight. The highly practical TCM function allows you to switch from TTL settings to manual values with a single click, making it easier to maintain a perfectly balanced exposure and perform further precise adjustments.

2.4G wireless system with a 100-meter range

The NEEWER QZ-C uses the NEEWER 2.4G Wireless Q System, which ensures stable communication at distances of up to 100 meters. Support for 5 groups (A-E), 32 channels, and IDs from 01 to 99 allows you to build complex lighting setups without the risk of interference. The free channel scanning feature automatically finds the best transmission settings.

Compatibility with NEEWER and Godox lights

The trigger works with many NEEWER lights, including the Q200, Q4, Q6, Q120, Z1, Z2, Z2PRO, Z3, and Z880 models. After switching to X Mode and updating the software, it can also control select Godox strobes compatible with the 2.4G X System. This makes it easy to integrate it into your existing lighting setup and gives you greater flexibility while working.

Modeling light and zoom control

From the screen, you can conveniently turn on and adjust the brightness of the modeling light, as well as set the flash zoom in automatic or manual mode within a range of 20 to 200 mm. This allows you to precisely adjust the character and direction of the light to the scene being photographed, resulting in better results without having to approach the flash.

Built-in battery and compact design

The 3.7V lithium battery with a capacity of 1000 mAh provides 6 to 10 hours of operation, and a full charge via the USB-C port takes about 2.5 hours. The USB-C port is also used for firmware updates, ensuring compatibility with new devices. The lightweight design (60 g) and quick-release hot shoe

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

mount ensure comfortable use and a stable attachment to the camera.

Included

- 1 x QZ Flash Trigger
- 1 x USB Type-C Cable
- 1 x Storage Pouch

Manufacturer	NEEWER
Model	QZ-C
Device Type	Wireless TTL Flash Trigger
Compatibility	Compatible with Canon cameras
Built-in Battery	3.7 V, 1000 mAh, 3.7 Wh
Charging Time	2.5 hours
Automatic TTL Flash Metering	Yes
Manual Flash Mode (M)	Yes
Stroboscopic flash (Multi)	Yes
First-curtain sync	Yes
Second-curtain sync	Yes
High-speed sync (HSS)	Yes (up to 1/8000 s)
Flash exposure compensation (FEC)	±3 EV (adjustable in 1/3 EV steps)
Beep Control	Ability to control the flash ready beep from the trigger
ZOOM Settings	Auto (AUTO), Manual (20–200 mm)
TCM Function	Conversion of automatic TTL values to manual (M) values
Firmware Update (Firmware)	Via USB-C port
Settings memory function	Yes
Display screen	Color HD OLED touchscreen with brightness adjustment

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Transmission range	0-100 m
Channels	32 (CH1-CH32)
Groups / Wireless ID	5 groups (A, B, C, D, E) / ID: OFF (disabled), 01-99
Dimensions	64 × 41 × 38 mm
Weight	60 g

GPSR Link: <https://psr->

assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf, Gross weight: 170, Net weight: 150, Box length: 8,50, Box width: 6,50, Box height: 8,00

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950