



InLine Slim SAS cable, SFF-8654 to 4x SATA 7- pin, 12Gb/s, 1m

Model: 27646B

Manufacturer: INLINE

EAN: 4043718288656

Product Code: 760975

R1,500

Efficient data connection: Connects SAS controllers to up to four SATA devices – ideal for professional storage environments.

High transfer rate: Supports up to 12Gb/s per channel for fast and stable data transfer.

Space-saving design: Slim SAS design allows for optimal cable routing even in compact server enclosures.

Secure connection: With locking clip on the SFF-8654 connector for reliable connection in continuous use.

Broad compatibility: SFF-8654 to 4x SATA 7-pin – suitable for use with HBA cards, RAID controllers, JBOD, and DAS.

The InLine® Slim SAS cable with an SFF-8654 4i connector on one end and four SATA 7-pin connectors on the other is specially designed for professional use in server and storage environments. It enables the connection of modern SAS controllers with up to four SATA hard drives or SSDs. Thanks to support for up to 12 Gb/s per channel, fast and stable data transfer is possible –

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

even with data-intensive applications. The robust locking clip on the Slim SAS connector ensures a secure fit and protects against accidental removal. The space-saving Slim SAS design also allows for flexible cable routing, even in confined spaces. The cable is ideal for use in JBOD, DAS, or other enterprise storage solutions. Its high-quality workmanship and precise specifications make it the optimal choice for professional applications.

Connector type: Slim SAS 4i (SFF-8654) to 4x SATA 7-pin

Transfer rate: Up to 12Gb/s per channel

With locking clip: For secure connection

Specification: Compliant with SAS 4.0 SFF-8654

Use: Internal connection cable for servers, JBOD, DAS