




CASE FAN

120MM

WRL/G99.12TLLCD1W1B.0

LIAN LI

Model: G99.12TLLCD1W1B.00

Manufacturer: LIAN LI

EAN: 4718466017253

Product Code: 761880

R1,534

The UNI FAN TL Wireless and TL LCD Wireless feature LIAN LI's innovative wireless sync technology, utilizing a 2.4GHz wireless signal to control lighting effects and fan speed to further improve the PC building experience while delivering efficient cooling, dazzling lighting, and quiet operation.

WIRELESS TRANSMISSION, EASY INSTALLATION

By adopting 2.4GHz wireless technology, the UNI FAN TL Wireless Series eliminates the need for traditional hub connections, significantly simplifying the installation process and enhancing user experience.

INNOVATIVE L-WIRELESS CONTROLLER

Instead of using the traditional connection method, the L-Wireless Sync Controller controls both lighting and fan speeds without connecting the cable to the controller.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The fans can be powered via a 4-PIN fan header on the motherboard or a SATA power cable. For the LCD versions, a USB 2.0 9-PIN cable connection to the motherboard is required to set the LCD screen.

The LCD and non-LCD versions use different receivers. For mixed clusters, use the LCD version receiver.

Each fan group requires connection to either a 12V PWM header or a 1-to-3 SATA splitter cable.

- UNI FAN TL Wireless: PWM cable powers the LED and motor.
- UNI FAN TL LCD Wireless: PWM cable powers the LED and motor; USB cable transmits LCD signals and provides LCD power.

The cable length can be shortened with the organizer on the receiver.

The transmission logic between the USB port and the LCD has been optimized, enabling the use of an additional USB splitter cable to the USB 2.0 or 3.0 port on the motherboard:

- USB splitter cable without SATA for additional power (e.g., LIAN LI USB 2.0 1-to-3 HUB): Supports up to 6 TL LCD wireless fans.
- USB splitter cable with SATA for additional power (e.g., LIAN LI Edge hub): Supports up to 9 TL LCD wireless fans.
- Furthermore, a single motherboard can support up to 20 UNI FAN TL LCD wireless fans.

ONE CONTROLLER FOR ALL

The L-Wireless Controller supports UNI FAN TL Wireless, UNI FAN SL Wireless, Strimer Wireless, and more future products.

The L-Wireless Controller can transmit signals to up to 10 channels.

Each group of wireless fans occupies one channel, while each Strimer Wireless uses an additional channel.

When all 10 channels are connected to the UNI FAN TL (non-LCD) wireless, the L-Wireless Controller

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

can manage up to 40 fans at a time.

In the future, the L-Wireless Controller will also be compatible with more LIAN LI wireless devices. With this controller, you can create a stunning and streamlined LIAN LI ecosystem that combines beauty and simplicity!

PERSONALIZED REMIX, STYLE ON DISPLAY

UNI FAN TL Wireless and TL LCD wireless now can be mix-matched into a group, offering versatile configurations and empowering creativity.

PRACTICAL AND STYLISH LCD SCREEN

The UNI FAN TL LCD Wireless carries forward the legacy of the world's first LCD-equipped fan. It features a 1.6" circular LCD screen with 60Hz refresh rate (upgraded from 30Hz) that integrates seamlessly with LIAN LI's L-Connect 3 software, offering exceptional customizability.

PERFORMANCE DETAIL AT A GLANCE

Monitor CPU and GPU temperature and load with new built-in animated hardware sensors displayed directly on the screen. For clusters of 3 LCD fans, multiple data points can be displayed simultaneously.

COMBINATION OF PERFORMANCE AND AESTHETICS

The UNI FAN TL Wireless uses LCP material for fan blades, a copper center shaft, and FDB bearings with 9 tightly aligned blades (0.65mm gap), ensuring a striking look without compromising on performance.

The UNI FAN TL Wireless offers performance on par with the UNI FAN P28, the top performer in the UNI FAN lineup.

SOPHISTICATED CONTINUOUS RGB LIGHTING

Each UNI FAN TL Wireless series fan has 26 LEDs with a wide infinity mirror on the 2 sides of the fan frame that wraps around the edges of the anti-vibration pad.

SEAMLESS SOFTWARE

Able to set different fan speeds for each fan cluster to optimize different scenarios of use providing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

flexibility for radiator or case fan needs with L-Connect 3.

L-Connect 3 offers a variety of features, such as grouping, naming, and sorting fans for more intuitive management, providing diverse functionality and user-friendly design.

- L-Wireless Sync supported (required for use)
- UNIFAN interlocking system for streamlined cable management
- Available in two versions: LED and LCD (mixable in a single cluster)
- Two light zones for an enhanced visual experience
- Full software control for fan speed, lighting effects, and LCD screen display via L-Connect 3
- Noise-optimized and performance-oriented fan
- LCP (liquid crystal polymer) fan blades are used for tight tolerance

Summary: Lian Li Uni Fan TL. Type: Fan, Fan diameter: 12 cm, Rotational speed (min): 0.2 RPM, Rotational speed (max): 2300 RPM, Maximum air pressure: 2.66 mmH2O, Bearing type: Fluid Dynamic Bearing (FDB). Voltage: 12 V. Product colour: Black | Vendor Homepage: <https://lian-li.com/product/uni-fan-tl-wireless/> | Fan diameter: 120 | Type: Fan | Suitable location: Computer case | Rotational speed (min): 0.2 | Rotational speed (max): 2300 | Noise level (high speed): 34 | Maximum airflow: 83.4 | Maximum air pressure: 2.66 | Pulse-width modulation (PWM) support: Yes | Bearing type: Fluid Dynamic Bearing (FDB) | Quantity per pack: 1 | Product colour: Black | Material: Thermoplastic polyester (PBT) | Number of fans: 1 | Illumination LED: Yes | Illumination colour: Multi | Fan connector: 4-pin | Power supply: 4.5 | Voltage: 12 | LED voltage: 5 | Fan dimensions (W x D x H): 120 x 124 x 28 | Unit Calculated Weight: 0.37 | Product Net Weight: 0.22 | Unit Calculated Volume: 0.001458 | Units per Shipping Box: 30 | Unit Width: 4.5 | Units per Pallet: 0 | Shipping Box Height: 21 | Unit Depth: 13.5 | Unit Height: 18 | Name: CASE FAN 120MM WRL/G99.12TLLCD1W1B.00 LIAN LI | Model name: UNI FAN TL

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950