



Power Supply GIGABYTE GP- P550SS ICE ATX PC 155-240 V 550 W GP- P550SSICE



Model: GP-P550SS ICE

Manufacturer: GIGABYTE

EAN: 4719331554910

Product Code: 761903

R1,487

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

- Ice white aesthetics
- 80 PLUS Silver certified (230V EU)
- Support Intel ATX 3.0 standard (compatible with ATX 3.1)
- 120mm Fluid Dynamic Bearing (FDB) Fan
- Flat cable design

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Powerful single +12V rail
- OVP/OPP/SCP/UVP/OCP/OTP protection

Summary: GIGABYTE P550SS ICE Power Supply - PCIe 5.0, 80 PLUS Silver, 120mm Fan, ATX 3.0 compatible, EU Plug. Total power: 550 W, AC input voltage: 155-240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Silver. Product colour: White, Cooling type: Active, Fan diameter: 12 cm. Width: 140 mm, Depth: 150 mm, Height: 86 mm | Vendor Homepage: <https://www.gigabyte.com/Power-Supply/GP-P550SS-ICE> | Total power: 550 | AC input voltage: 155-240 | AC input frequency: 50/60 | Input current: 6.3 | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 | Combined power (+12V): 549.6 | Combined power (+5V): 100 | Combined power (-12V): 3.6 | Combined power (+5Vsb): 15 | Max output current (+3.3V): 20 | Max output current (+12V): 45.8 | Max output current (+5V): 20 | Max output current (-12V): 0.3 | Max output current (+5Vsb): 3 | Efficiency: 90 | Hold time: 16 | Power Good signal delay range: 100 - 150 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Motherboard power connector: 20+4 pin ATX | Motherboard power cable length: 600 | Number of SATA power connectors: 5 | Peripheral (Molex) power connectors (4-pin): 4 | PCI Express power connectors (6+2 pin): 2 | CPU power connector (4+4 pin): Yes | ATX power connector (20+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 2 | PCI Express connector: Yes | Cabling type: Non-Modular | 80 PLUS certification: 80 PLUS Silver | Purpose: PC | Power supply unit (PSU) form factor: ATX | ATX version: 3.1 | Bearing technology: Ball bearing | Mean time between failures (MTBF): 100000 | Product colour: White | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | Fan location: Top | On/off switch: Yes | Width: 140 | Depth: 150 | Height: 86 | Weight: 1950 | Package width: 254 | Package depth: 206 | Package height: 117 | Package weight: 2110 | Package type: Box | Warranty period: 3 | Unit Calculated Weight: 2.19 | Product Net Weight: 2 | Unit Calculated Volume: 0.007502 | Units per Shipping Box: 5 | Unit Width: 22.6 | Shipping Box Height: 27.5 | Unit Depth: 25.5 | Unit Height: 11.8 | Name: CASE PSU ATX3.0 550W/GP-P550SS ICE GIGABYTE | Model name: GP-P550SS ICE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950