

WRL CAMERA 5MP PT IR LED DOME/P5B-PV DAHUA



Model: P5B-PV

Manufacturer: DAHUA

EAN: 6923172563491

Product Code: 762025

R1,417 ~~R1,686~~

The Picoo series of small PT cameras raises the bar on performance. After detecting an intrusion, it triggers sound and light alarms, and then instantly relays vital information on the intrusion to the mobile client, keeping you informed no matter where you are. It supports two-way talk, allowing you to communicate with people in front of the camera in real time. It also can record full-color videos and information of key events using Smart Dual Illuminators, effectively reducing light pollution.

Summary: Dahua Technology P5B-PV. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired & Wireless. Mounting type: Ceiling/wall, Product colour: White, Form factor: Spherical. Lens viewing angle, horizontal: 78°, Lens viewing angle, vertical: 40°, Lens viewing angle, diagonal: 93°. Sensor type: CMOS, Optical sensor size: 25.4 / 3 mm (1 / 3"). Night vision distance: 30 m | Vendor Homepage: <https://www.dahuasecurity.com/es/products/All-Products/Network-Cameras/Wireless-Series/Outdoor-Camera/Picoo-Series/P5B-PV> | Connectivity technology: Wired & Wireless | Placement supported: Indoor & outdoor | Type: IP security camera |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Form factor: Spherical | Housing material: Plastic | International Protection (IP) code: IP66 | Mounting type: Ceiling/wall | Product colour: White | Camera shutter speed: 1/3 - 1/100000 | Camera shutter type: Electronic | Lens viewing angle, diagonal: 93 | Lens viewing angle, horizontal: 78 | Lens viewing angle, vertical: 40 | Pan range: 0 - 355 | Tilt angle range: 0 - 90 | Optical sensor size: 1/3 | Sensor type: CMOS | Maximum aperture number: 1.6 | Number of lenses: 1 | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 2 | Bit rate: H.265: 80 kbps-4096 kbps | Digital Wide Dynamic Range (DWDR): Yes | Frame rate: 30 | Maximum resolution: 2880 x 1620 | Smart IR: Yes | Supported graphics resolutions: 2880 x 1620/640 x 360 | Total megapixels: 5 | Video compression formats: H.265 | Built-in microphone: Yes | Built-in speaker(s): Yes | Voice codecs: G.711a | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 6 (802.11ax) | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Human detection/Vehicle detection | Video motion detection: Yes | Management software: DMSS | Smartphone/tablet remote support: Yes | DC output voltage: 12 | Power consumption (max): 4.56 | Power consumption (typical): 1.68 | Power source type: DC | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -20 - 50 | Mobile operating systems supported: Android/iOS | Depth: 116 | Height: 139 | Weight: 425 | Width: 138 | Compliance certificates: CE | Number of cameras: 1 | Product Net Weight: 0.425 | Shipping Box Height: 37 | Unit Calculated Volume: 0.005114 | Unit Calculated Weight: 0.804 | Units per Shipping Box: 24 | Model: P5B-PV

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950