

WRL CAMERA 5MP BULLET WIFI/F5D-IL- 0280B DAHUA



Model: F5D-IL-0280B

Manufacturer: DAHUA

EAN: 6939554980404

Product Code: 762093

R1,345 R1,593

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Summary: Dahua Technology Entry DH-IPC-HDW1230T1-S4. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Minimum illumination: 0.01 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 105°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"), Number of effective pixels (H x V): 1920 x 1080 pixels. Detect distance: 37.3 m, Observe distance: 14.9 m, Recognize distance: 7.5 m | Vendor Homepage: <https://www.dahuasecurity.com/> | Connectivity technology: Wired | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Placement supported: Indoor & outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Form factor: Dome | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Mounting type: Ceiling | Product colour: White | Adjustment shutter speed: Auto/Manual | Angle of rotation: 360 | Camera pan

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

control: Yes | Camera shutter speed: 1/3-1/100000 | Camera shutter type: Electronic | Camera tilt control: Yes | Lens viewing angle, diagonal: 125 | Lens viewing angle, horizontal: 105 | Lens viewing angle, vertical: 57 | Minimum illumination: 0.01 | Pan range: 0 - 355 | Tilt angle range: 0 - 78 | White balance: Auto/Manual/Natural/Outdoor | Number of effective pixels (H x V): 1920 x 1080 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 0.5 | Detect distance: 37.3 | Fixed focal length: 2.8 | Fixed focus: Yes | Identify distance: 3.7 | Maximum aperture number: 2 | Number of lenses: 1 | Observe distance: 14.9 | Recognize distance: 7.5 | LED type: IR | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 1 | Back Light Compensation (BLC): Yes | Digital Wide Dynamic Range (DWDR): Yes | Frame rate: 30 | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Maximum resolution: 1920 x 1080 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Supported video modes: 1080p/720p | Total megapixels: 2 | Video formats supported: H.264/H.265/M-JPEG | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Supported network protocols: IPv4; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast | Wi-Fi: No | Built-in HDD: No | Internal memory: 64 | ROM capacity: 16 | Ethernet LAN (RJ-45) ports: 1 | Motion sensor: Yes | Management software: Smart PSS; DSS; DMSS | Web browser: Yes | DC output voltage: 12 | Power consumption (typical): 4.3 | Power source type: DC,PoE | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -40 - 60 | Storage relative humidity (H-H): 0 - 95 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Diameter: 109 | Height: 85.5 | Weight: 240 | Package weight: 370 | Number of cameras: 1 | Product Net Weight: 0.331 | Shipping Box Height: 27 | Unit Calculated Volume: 0.003758 | Unit Calculated Weight: 0.6 | Units per Pallet: 0 | Units per Shipping Box: 20 | Model: F5D-IL-0280B | Model name: DH-IPC-HDW1230T1-S4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950