

WRL CAMERA 3MP PT IR LED DOME/P3B-PV DAHUA



Model: P3B-PV

Manufacturer: DAHUA

EAN: 6923172563484

Product Code: 762192

R1,272 R1,500

The Picoo series of small PT cameras raises the bar on performance. After detecting an intrusion, it triggers sound and light alarms, and then instantly relays vital information on the intrusion to the mobile client, keeping you informed no matter where you are. It supports two-way talk, allowing you to communicate with people in front of the camera in real time. It also can record full-color videos and information of key events using Smart Dual Illuminators, effectively reducing light pollution.

Summary: Dahua Technology DH-P3B-PV. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired & Wireless. Mounting type: Ceiling/wall, Product colour: White, Form factor: Turret. Angle of rotation: 180°, Lens viewing angle, horizontal: 87°, Lens viewing angle, vertical: 44°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Night vision distance: 30 m, LED type: IR/White | Vendor Homepage: <https://www.dahuasecurity.com> | Auto-tracking: Yes | Built-in light: Yes | Connectivity technology: Wired & Wireless | Day/night mode: Yes | Placement supported: Outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Form factor:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Turret | Housing material: Plastic | International Protection (IP) code: IP66 | Mounting type: Ceiling/wall | Product colour: White | Adjustment shutter speed: Auto/Manual | Angle of rotation: 180 | Camera shutter speed: 1/3 s-1/100,000 s | Camera shutter type: Electronic | Lens viewing angle, diagonal: 105 | Lens viewing angle, horizontal: 87 | Lens viewing angle, vertical: 44 | Pan range: 0 - 355 | Tilt angle range: 0 - 90 | Optical sensor size: 1/2.7 | Sensor type: CMOS | Maximum aperture number: 1.6 | LED type: IR/White | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 4 | Bit rate: 80 kbps-4096 kbps | Digital Wide Dynamic Range (DWDR): Yes | Frame rate: 30 | Maximum resolution: 2304 x 1296 | Total megapixels: 3 | Video compression formats: H.265 | Video streaming: Yes | Built-in microphone: Yes | Built-in speaker(s): Yes | Voice codecs: G.711a | Bluetooth: Yes | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 6 (802.11ax) | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Human detection/Vehicle detection | DC output voltage: 12 | Power consumption (max): 4.56 | Power consumption (typical): 1.56 | Power source type: DC | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -20 - 50 | Mobile operating systems supported: Android/iOS | Depth: 138 | Height: 139 | Weight: 425 | Width: 116 | Number of cameras: 1 | Product Net Weight: 0.425 | Shipping Box Height: 37 | Unit Calculated Volume: 0.005025 | Unit Calculated Weight: 0.806 | Units per Shipping Box: 24 | Model: P3B-PV

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950