



Power Supply XILENCE 400 Watts PFC Active XN041

Model: XN041

Manufacturer: XILENCE

EAN: 4044953500213

Product Code: 762254

R1,218

Performance C Series

The new Xilence Performance C series is focusing on the essentials. Designed for office and home computers, the new Performance C series delivers stable voltages with high efficiency (ErP2014). This guarantees a considerably low fan noise. Four built-in safety circuits ensure safe operation at all times.

- extremely silent cooling: large 120mm fan
- excellent air flow design for a better heat dissipation
- following safety design:
 - Over Voltage Protection (OVP)
 - Under Voltage Protection (UVP)
 - Short Circuit Protection (SCP)
 - Over Load Protection (OLP)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- low stand-by consumption
- complies with ErP2014 norm

Summary: Xilence Performance C XP400R6. Total power: 300 W, AC input voltage: 110 - 240 V, Peak power: 400 W. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX. Product colour: Black, Fan diameter: 12 cm, Number of fans: 1 fan(s). Package width: 230 mm, Package depth: 165 mm, Package height: 100 mm | Vendor Homepage: <https://www.xilence.de/en/products/power-supplies/performance-c-series/performance-c-series.html> | Total power: 300 | Peak power: 400 | AC input voltage: 110 - 240 | AC input frequency: 50 | Power Factor Correction (PFC) type: Active | Max output current (+3.3V): 10 | Max output current (+12V): 15 | Max output current (+5V): 10 | Max output current (-12V): 0.3 | Max output current (+5Vsb): 3 | Power protection features: Over voltage/Overload/Short circuit/Under voltage | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 3 | PCI Express power connectors (6-pin): 1 | CPU P4 connector (4-pin): 1 | Cabling type: Non-Modular | Purpose: PC | Power supply unit (PSU) form factor: ATX | ATX version: 2.31 | Product colour: Black | Fan diameter: 120 | Number of fans: 1 | Package width: 230 | Package depth: 165 | Package height: 100 | Package weight: 1420 | Package type: Box | Harmonized System (HS) code: 84733020 | Unit Calculated Weight: 1.52 | Product Net Weight: 1.4 | Unit Calculated Volume: 0.004732 | Units per Shipping Box: 10 | Unit Width: 3.5 | Units per Pallet: 0 | Shipping Box Height: 26 | Unit Depth: 52 | Unit Height: 26 | Name: CASE PSU ATX2.3 400W/XP400R6 XN041 XILENCE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950