



CASE FAN 120MM/G99.12SL V.0 LIAN LI



Model: G99.12SL1W1W.00

Manufacturer: LIAN LI

EAN: 4718466016706

Product Code: 762420

R1,120

The UNI FAN SL Wireless series has made another revolutionary breakthrough in making cable management easier and unifying controllers across different devices. The UNI FAN SL Wireless utilizes a 2.4 GHz wireless signal to control its lighting effects and fan speed to further improve your PC building experience.

AVAILABLE IN TWO VARIATIONS

TWO ORIENTATIONS

TWO COLORS

UNI FAN Wireless Series includes both LCD and LED versions. Both are available in black and white, with options for standard and reverse blade configurations meeting the diverse needs of users.

WIRELESS CONTROL, EASY INSTALLATION

The revolutionary 2.4GHz L-wireless controller greatly simplifies the installation experience of UNI FAN SL Wireless Series.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

SIMULTANEOUS CONTROL

This powerful controller supports the transmission of 10 channels simultaneously.

Each group of fans occupies one channel, ensuring stable control for multiple groups of fans, all within the installation limits of your standard PC. Plus, it's fully compatible with the latest Strimer Wireless, allowing you to use the extra channels for other devices.

In the future, the L-Wireless Controller will also be compatible with all LIAN LI wireless devices. With this controller, you can create a stunning and streamlined LIAN LI ecosystem that combines beauty and simplicity!

PERSONALIZED REMIX, STYLE ON DISPLAY

UNI FAN SL Wireless LED and LCD now can be mix-matched into a group, empowering users to unleash their creativity and freely combine them.

ADDITIONAL LIGHT STRIP, ENHANCED VISUAL EXPERIENCE

The UNI FAN SL Wireless series not only shows innovation in functionality but also enhances its visual appeal. Each side of the fan now features an additional light strip, increasing the total number of LEDs to 40. This enables duo-zoned lighting adjustments, delivering a more dynamic and versatile visual experience that truly stands out.

PRACTICAL AND STYLISH LCD SCREEN

Building on the unique design of the UNI FAN TL LCD, the world's first LCD-integrated fan, the UNI FAN SL Wireless LCD features the same 1.6" LCD screen. With seamless integration into the L-Connect 3 software, users have the flexibility to customize the display to showcase their preferred content, offering a highly personalized experience.

PERFORMANCE DETAIL AT A GLANCE

Monitor the temperature and load of your CPU and GPU, as well as the fan speed, instantly with built-in hardware monitor dashboards on the screen. In a scenario of a cluster of 3 LCD fans, you can simultaneously monitor a variety of data, stay informed and in control of your system.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Preset Animations

L-Connect 3 offers several preset animations. Whether your fans are arranged vertically or horizontally, there are corresponding animation effects available for you to use.

Upload Your Style

Elevate your system's style by uploading your own personalized MP4 / GIF / JPG / PNG. You can also take advantage of the screen record/screen shot function to make content uploading easier than ever.

BREEZE YOUR SYSTEM

UNI FAN SL Wireless series features FDB bearing, ensuring long-term high-speed operation at a lower noise level. LCD and LED versions can reach fan speeds of up to 1900 RPM and 2100 RPM, respectively.

- L-Wireless Sync supported (required for use)
- UNIFAN interlocking system for streamlined cable management
- Available in two versions: LED and LCD (mixable in a single cluster)
- Two light zones for an enhanced visual experience
- Full software control for fan speed, lighting effects, and LCD screen display via L-Connect 3
- Optimized for airflow and noise, making it ideal for PC case fans

Summary: Lian Li UNI FAN SL Wireless 120. Type: Fan, Fan diameter: 12 cm, Maximum air pressure: 2.44 mmH₂O, Bearing type: Fluid Dynamic Bearing (FDB). Voltage: 5 - 12 V. Product colour: White | Vendor Homepage: <https://lian-li.com/product/uni-fan-sl-wireless/?cn-reloaded=1> | Fan diameter: 120 | Type: Fan | Suitable location: Computer case | Noise level (high speed): 28.5 | Maximum airflow: 64.05 | Maximum air pressure: 2.44 | Pulse-width modulation (PWM) support: Yes | Bearing type: Fluid Dynamic Bearing (FDB) | Quantity per pack: 1 | Fan speed (max): 2000 | Fan speed (min): 400 | Product colour: White | Material: Polybutylene terephthalate (PBT) | Number of fans: 1 | Illumination LED: Yes | Illumination colour: Multi | Fan connector: 4-pin | Power consumption (typical): 1.8 | Voltage: 5 - 12 | Rated voltage: 40 | Package type: Box | Unit Calculated Weight: 0.29 | Product Net Weight: 0.2 | Unit Calculated Volume: 0.001144 | Units per Shipping Box: 30 | Units per Pallet: 0 | Shipping Box Height: 21 | Name: CASE FAN 120MM/G99.12SL1W1W.00 LIAN LI | Model: UNI FAN SL Wireless 120 | Model name: 12SL1W1W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950