

Axagon PCEE-G25 PCIe - 2.5 Gigabit Ethernet adapter Realtek 8125, PXE, w. SP & LP

Axagon PCEE- G25 PCIe - 2.5 Gigabit Ethernet adapter Realtek 8125, PXE, w. SP & LP



Model: PCEE-G25

Manufacturer: AXAGON

EAN: 8595247906458

Product Code: 762831

R875 ~~R943~~

AXAGON PCEE-G25 PCI-Express network card adds high speed 2.5 Gigabit Ethernet connection to your desktop computer. Backward compatible with Gigabit and 10/100Base-T networks.

The network card is equipped with Realtek RTL8125B chipset. It ensures seamless compatibility with most operating systems. The LAN adapter supports network boot (PXE) and also Realtek Dragon Software for settings management and automatic bandwidth control.

2.5G Ethernet network card expands the computer with a very fast network connection, adds the missing RJ-45 connector, add another network card or replaces the original defunct network connection. The advantage of the IEEE 802.3bz standard is that common Cat 5e and Cat 6 Ethernet cables up to 100 m long can be used for speed of 2.5 Gb/s.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

In addition to an adapter with a standard size bracket, the package also includes a low profile bracket which allows the mounting into low profile cases.

Input:

- PCI-Express 2.1 interface, PCI-Express 1.0a / 1.1 / 2.0 / 3.0 compatible.
- Number of lines 1-Lane (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
- A bandwidth of 1-Lane PCI-Express 2.1 bus 5 Gb/s.

Output:

- Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
- Supported transmission rates for the Ethernet interface 10/100/1000/2500 Mb/s.
- Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3bz 2.5GBase-T specifications.

Other features:

- Full Plug and Play support.
- 10/100/1000/2500 Mbit/s auto-detection.
- Supports Microsoft NDIS5, NDIS6 Checksum Offload (IPv4, IPv6, TCP, UDP) to reduce processor load.
- Supports Segmentation Task-offload (Large send v1 a Large send v2).
- Supports full-duplex transmission s IEEE 802.3x flow control.
- Supports IEEE 1588v1, IEEE 1588v2, IEEE 802.1AS – time synchronization.
- Supports IEEE 802.1Qav – routing and queuing of time-sensitive flows.
- Supports IEEE 802.1P Layer 2 priority encoding.
- Supports IEEE 802.1Q VLAN tagging.
- Supports IEEE 802.1ad Double VLAN.
- Supports IEEE 802.3az-2010 (EEE) Energy Efficient Ethernet - reduce power consumption at standby.
- Supports quad core Receive-Side Scaling (RSS).
- Supports Auto MDI/MDIX - crossover detection and auto-correction eliminate the need for crossover cables.
- Supports hardware ECC (Error Correction Code) function.
- Supports hardware CRC (Cyclic Redundancy Check) to detect transmission errors.
- Supports Pair Swap/Polarity/Skew Correction.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- LED for indicating network activity.
- The Realtek RTL8125B chipset is used.

Wake-on-LAN feature support in different modes:

- Supports sleep mode and remote Wake Up via AMD Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and Link Change Wake-up.
- Supports ECMA-393 proxZzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.
- RealWoW! technology support allows remote wake up over the Internet.

Advanced Power Management features:

The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.

- Supports Advanced Configuration Power management Interface (ACPI).
- Supports Power Management offload (ARP & NS).
- Supports Microsoft Always On Always Connected (AOAC).
- Supports Operating System-directed Power Management (OSPM).
- Supports PCI MSI (Message Signaled Interrupt) and MSI-X.

Supported operating systems:

MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 and later (supported are all 32- and 64-bit versions of OS Windows), MS DOS, MacOS X 10.7 and later, Linux kernel 2.4.x and later, FreeBSD 7.x / 8.0 / 9.0, SCO Unix 5.0.6 / 5.0.7, Novell server OS 5.x / 6.x, Novell client for DOS (ODI driver).

Package contains:

- PCI-Express Gigabit Ethernet card with a standard bracket,
- low profile bracket,
- printed installation guide in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950