

**Hikvision Pro
Series DS-
2CD2066G2H-
IU(2.8mm)(eF)/BLACK
Indoor/Outdoor
IP Security
Bullet Camera
3200 x 1800 px
Ceiling/Wall**



Model: DS-2CD2066G2H-IU

Manufacturer: HIKVISION

EAN: 6942160480398

Product Code: 786571

R4,632

Number of simultaneous live view channels: 6 channels | Languages support: Multi | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Lens viewing angle, vertical: 60° | Infrared (IR) cut-off filter: Yes | Sample rates: 8 - 48 kHz | Digital watermark: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Password reset via email: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Intelligent Video Surveillance (IVS) system features: Scene change | Image quality adjustment: Sharpness | Number of lenses: 1 | Built-in HDD: No | User access level: Administrator, Operator, User | Audio formats supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

G.722.1 | Sensor type: CMOS | Image quality adjustment: Saturation | Audio formats supported: AAC-LC | Progressive scan: Yes | Maximum aperture number: 1 | Video compression formats: H.265+ | Intelligent Video Surveillance (IVS) system features: Human detection | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Region entrance detection | Intelligent Video Surveillance (IVS) system features: Intrusion | Bit rate range: 8 - 320 Kbit/s | IP address filtering: Yes | Intelligent Video Surveillance (IVS) system features: Region exiting detection | Heartbeat: Yes | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Region of Interest (ROI) encoding: Yes | DC output current: 0.58 A | Video compression formats: H.264+ | Audio formats supported: MP2L2 | Noise reduction: Yes | Lens viewing angle, diagonal: 143.5° | Audio formats supported: G.726 | Active tampering alarm: Yes | Mirror: Yes | Video compression formats: H.264 | HTTPS encryption: Yes | Digest authentication: Yes | Recognize distance: 12 m | Image quality adjustment: Contrast | Number of users: 32 user(s) | Video motion detection: Yes | Privacy masking: Yes | Video compression formats: M-JPEG | Video compression formats: H.265 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Day/night mode: Yes | Infra-red wavelength: 850 nm | Lens viewing angle, horizontal: 114.8° | Mounting type: Ceiling/wall | DC output voltage: 12 | Image quality adjustment: Brightness | Password protection: Yes | Observe distance: 25 m | Placement supported: Indoor & outdoor | Pixel counter: Yes | Night vision: Yes | Noise reduction technology: 3D noise reduction | Identify distance: 6 m | Dynamic range: 120 dB | Detect distance: 64 m | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Protection features: Water resistant | Bluetooth: No | Protection features: Dust resistant | Connectivity technology: Wired | Tilt angle range: 0 - 90° | Form factor: Bullet | Package width: 234 mm | Number of cameras: 1 | Reset button: Yes | Camera shutter speed: 1/3 s - 1/100000 | Power source type: DC, PoE | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1280 x 720 (HD 720) | Angle of rotation: 360° | Audio formats supported: PCM | Diameter: 7.44 cm | Supported graphics resolutions: 3200 x 1800 | Maximum resolution: 3200 x 1800 pixels | Lens mount interface: M12 | Package height: 117 mm | Operating temperature (T-T): -30 - 60 °C | Wide Dynamic Range (WDR): Yes | Card reader integrated: Yes | Product colour: Black | Compatible memory cards: MicroSD (TransFlash) | Power consumption (max): 8.5 W | International Protection (IP) code: IP67 | Operating relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Wi-Fi: No | Package weight: 815 g | Highlight Compensation (HLC): Yes | Package depth: 120 mm | Storage temperature (T-T): -30 - 60 °C | Bit rate: 32 Kbps - 16 Mbps | Storage relative humidity (H-H): 0 - 95% | Video formats supported: H.265+ | Security algorithms: EAP-LEAP | Video formats supported: H.265 | Compatible memory cards: MicroSDXC |

Type: IP security camera | Video formats supported: M-JPEG | Security algorithms: TLS | Audio

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

formats supported: G.711 | Depth: 179.2 mm | Networking standards: IEEE 802.3af | Housing material: Metal | Video formats supported: H.264+ | LED type: IR | Pan range: 0 - 360° | Weight: 505 g | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Minimum illumination: 0 lx | Networking standards: IEEE 802.1x | Night vision distance: 40 m | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 2688 x 1520 | Security algorithms: EAP-TLS | Built-in microphone: Yes | Compatible memory cards: MicroSDHC | Audio formats supported: MP3 | Total megapixels: 6 MP | Security algorithms: EAP-MD5 | Video formats supported: H.264 | Number of Privacy masking areas: 4 | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: RoHS | Audit log: Yes | Compliance certificates: CB | Compliance certificates: REACH | Compliance certificates: KC | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Compliance certificates: Electromagnetic Compatibility (EMC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950