

# HIKVISION DS- 2SE4C425MWG- E/26(F0) IP Camera



Model: DS-2SE4C425MWG-E/26(F0)

Manufacturer: HIKVISION

EAN: 6931847199630

Product Code: 791077

## R11,885

Zoom speed: 3.6 s | Product colour: White | Ethernet LAN: Yes | Product colour: Black | Operating relative humidity (H-H): 0 - 90% | Ethernet interface type: Fast Ethernet | Height: 375 mm | Quality of Service (QoS) support: Yes | Wide Dynamic Range (WDR): Yes | Compatible memory cards: MicroSDHC | Compatible memory cards: MicroSDXC | Compatible memory cards: MicroSD (TransFlash) | Maximum resolution: 3632 x 1632 pixels | Bit rate: 32 Kbps - 16 Mbps | International Protection (IP) code: IP66 | Tilt angle range: 0 - 90° | Protection features: Waterproof | Operating temperature (T-T): -30 - 65 °C | Weight: 2.4 kg | Card reader integrated: Yes | Connectivity technology: Wired | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 960 x 432 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3632 x 1632 | Ethernet LAN (RJ-45) ports: 1 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1200 x 536 | Supported graphics resolutions: 352 x 240 | Power consumption (max): 24 W | Type: IP security camera | Power source

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

type: PoE+, DC | Alarm input channels: 1 | Product diameter: 166 mm | Number of users: 32 user(s) | Video motion detection: Yes | Privacy masking: Yes | LED type: IR | Zoom capability: Yes | Maximum memory card size: 256 GB | Alarm output channels: 1 | Lens viewing angle, horizontal: 55 - 2.4° | Progressive scan: Yes | Client interoperability: iVMS-4200,Hik-Connect | Lens viewing angle, diagonal: 61.5 - 2.8° | Mounting type: Ceiling | Digital zoom: 16x | Password protection: Yes | Audio formats supported: MP2L2 | Audio formats supported: G.711 | Audio formats supported: AAC-LC | Audio formats supported: G.722.1 | Sensor type: CMOS | Optical zoom: 25x | Highlight Compensation (HLC): Yes | Video compression formats: M-JPEG | Frame rate: 25 / 30 fps | Alarm input/output: Yes | Digital watermark: Yes | Total megapixels: 6 MP | Day/night mode: Yes | Audio formats supported: G.726 | Audio formats supported: PCM | Camera shutter speed: 1 - 1/30000 s | Lens viewing angle, vertical: 33 - 1.4° | Number of cameras: 1 | Built-in speaker(s): Yes | Video compression formats: H.264 | Minimum illumination: 0 lx | Auto focus: Yes | Number of simultaneous live view channels: 20 channels | Night vision: Yes | Pan range: 360 | DC output voltage: 12 | Placement supported: Outdoor | IP address filtering: Yes | Supported network protocols: IPv4/IPv6, HTTP, HTTPS, QoS,802.1x, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour | PTZ control: Yes | Audio formats supported: MP3 | Region of Interest (ROI) encoding: Yes | Live view: Yes | Dynamic range: 120 dB | Video compression formats: H.265 | Preset programs quantity: 300 | PTZ status display: Yes | Automatic Network Replenishment (ANR): Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950