

Cudy LT400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G White



Model: LT400 OUTDOOR_EU

Manufacturer: CUDY

EAN: 6971690792916

Product Code: 791581

R1,965

VPN support: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier | PoE injector included: Yes | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Weight: 420 g | Windows operating systems supported: Windows 10 Pro x64 | Windows

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | Package weight: 794 g | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Ethernet LAN data rates: 10 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Product colour: White | Modulation: 64-QAM | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows XP Professional x64 | Package width: 324 mm | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 11 Enterprise | Reset button: Yes | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Operating relative humidity (H-H): 0 - 100% | Wake-on-LAN ready: Yes | Security algorithms: WPA | MAC address filtering: Yes | LED indicators: WLAN | Security algorithms: WPA3 | AC input voltage: 100 - 240 V | Ethernet LAN (RJ-45) ports: 1 | DHCP client: Yes | Operating temperature (T-T): -20 - 60 °C | Ethernet LAN data rates: 100 | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 11 | Storage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

relative humidity (H-H): 5 - 95% | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | AC input frequency: 50/60 Hz | Filtering: Yes | Antenna gain level (max): 5 dBi | Mounting kit: Yes | Security algorithms: WPA2 | Power source type: PoE | Supported network protocols: IPv4 / IPv6 | 2G standards: Edge | 4G standard: LTE-TDD & LTE-FDD | Quick installation guide: Yes | Firewall: Yes | Depth: 100 mm | Package depth: 107 mm | Internal memory: 64 MB | IP address filtering: Yes | Ethernet LAN: Yes | 2G standards: GSM | Mobile network generation: 4G | Product type: Desktop/pole router | Height: 53.7 mm | WLAN data transfer rate (max): 300 Mbit/s | Cables included: LAN (RJ-45) | Linux operating systems supported: Yes | Dual SIM support: No | SIM card type: NanoSIM | Wi-Fi Multimedia (WMM)/(WME): Yes | Wall mountable: Yes | Wi-Fi band: Single-band (2.4 GHz) | International Protection (IP) code: IP65 | Detachable antenna(s): Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | URL filtering: Yes | Output voltage: 24 V | Mac operating systems supported: Yes | WAN connection type: RJ-45 | 3G standards: WCDMA | Port forwarding: Yes | Width: 240 mm | Cabling technology: 10/100Base-T(X) | Antennas quantity: 4 | Dynamic DNS (DDNS): Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Flash memory: 8 MB | Port triggering: Yes | Package height: 86 mm | Wi-Fi standards: 802.11b | Ethernet WAN: Yes | Ethernet LAN interface type: Fast Ethernet | Universal Plug and Play (UPnP): Yes | Wi-Fi standards: 802.11g | IGMP snooping: Yes | USB port: No | SIM card slot: Yes | DMZ support: Yes | Antenna design: Internal & external | Number of guest networks (2.4 GHz):