



Power Bank EcoFlow RAPID 25000 mAh, 170W



Model: EFRAPID25K140WB-EU

Manufacturer: ECOFLOW

EAN: 4895251653831

Product Code: 805686

R2,808

EcoFlow RAPID Power Bank 25000 mAh, 170W

The EcoFlow RAPID Powerbank features a 25,000 mAh capacity, which, combined with its compact design, makes it great for work, travel and everyday use. It supports fast charging with up to 140 watts on a single port and 170 watts combined when using multiple outlets simultaneously. Whether you're charging a laptop, phone or tablet, the RAPID delivers full performance without compromise.

Fast charging for up to three devices

With two USB-C (Universal Serial Bus Type-C, a universal connector for data and power), one USB-A (Universal Serial Bus Type-A, a standard connector for data and charging) ports and a combined power of up to 170 watts, you can charge several devices simultaneously without losing speed. The maximum power of 140 watts on a single USB-C port is even enough to power modern laptops and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

camera equipment. It's ideal for people who value their time and don't want to wait for a free outlet!

Capacity that gives you freedom

The 25,000 mAh battery allows you to charge your smartphone, tablet or camera multiple times. That's enough energy to power a laptop on the road, for example. Importantly, the device meets airline safety standards, so you can easily take it on a plane with you.

Smart TFT display

The built-in TFT (Thin-Film Transistor) screen offers access to the most important information related to the operation of the powerbank. With its help you can quickly check, for example, the charge level, temperature or current power on each port. The display provides a clear, readable image from any angle and in any lighting conditions - even in bright sunlight!

Advanced protection

The powerbank is equipped with an advanced power management system, used in electric vehicles, among others. The device constantly monitors the charging process, protecting the battery from overheating, overcharging, over-discharging and short-circuiting. This allows you to use it in almost any conditions - without worrying about safety.

General

Manufacturer	EcoFlow
Model	EFRAPID25K140WB-EU
Total cell capacity	25000 mAh
Battery capacity	14500 mAh (5 V / 3 A)
Dimensions	157 x 53.8 x 48.8 mm
Weight	Approximately 565 g
Color	Black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Battery

Cell chemistry	Three-component lithium
Lifetime	Approximately 300 charge cycles (up to 80% capacity)
Battery type	Changhong Sanjie, INR21700-5000, 5*5000mAh
Number of cells	5 5000mAh 21700 batteries connected in series

Outputs

Available output ports	USB-C1 140 watts, USB-C2 140 watts, USB-A 33 watts, max total output power 170 watts.
USB-A output	33 W
USB-C output	140 W

Inputs

Input power	140 W
Charging via USB-C	Charging via multiple ports is not supported. The maximum input power per port (USB-C1 / USB-C2) is 140 watts.

Other

Management by application	No
Screen	TFT
Drop resistance	Up to 1m
Fire resistance	V0 class housing
Certification	EMC Class B

Temperature

Optimum operating temperature From 20°C to 30°C

Charging temperature From 0°C to 45°C

Discharge temperature From -10°C to 45°C

Capacity (mAh): 25000, Color: black, Charging power (W): 170, Wireless charging: No, GPSR Link: https://psr-assets.innpro.pl/gsm_accessories/sg_gsm_accessories_powerbanks.pdf, Net weight: 570, Box length: 10,20, Box width: 5,70, Box height: 17,50, Gross weight: 700, Information about data generation: <https://dataact.innpro.pl/ecoflow/4895251653831>