

NET CAMERA 12MP BULLET/HFW21249T-AS-IL-0280B DAHUA

NET CAMERA 12MP BULLET/HFW21249T- AS-IL-0280B DAHUA



Model: IPC-HFW21249T-AS-IL-0280B

Manufacturer: DAHUA

EAN: 6939554913884

Product Code: 811823

R5,912

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

- High-Quality Imaging with 12MP Resolution
- Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- Deep Learning-Based Human and Vehicle Classification
- Built-in Mic for Real-Time Audio Security
- Supports Max. 256G Micro SD card
- Efficient H.264+/H.265+ Compression Technology

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Rich Interface: Alarm: 1 in, 1 out; audio: 1 in, 1 out

Summary: Dahua Technology WizSense IPC-HFW21249T-AS-IL. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 112°, Lens viewing angle, vertical: 58°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.5 mm (1 / 2.5"). Signal-to-Noise Ratio (SNR) (panoramic camera): 56 dB | Vendor Homepage: <https://www.dahuasecurity.com/products/network-products/network-cameras/wizsense-2-series/smart-dual-light/ipc-hfw21249t-as-il=s2> | Form factor: Bullet | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Built-in light: Yes | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Minimum illumination: 0 | Angle of rotation: 360 | Lens viewing angle, horizontal: 112 | Lens viewing angle, vertical: 58 | Lens viewing angle, diagonal: 136 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic/Mechanical | Camera shutter speed: 1/3 - 1/100000 | Number of Privacy masking areas: 4 | Signal-to-Noise Ratio (SNR) (panoramic camera): 56 | Optical sensor size: 1/2.5 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 98.9 | Observe distance: 39.6 | Recognize distance: 19.8 | Fixed focus: Yes | Identify distance: 9.9 | Maximum aperture number: 1.6 | Closest focusing distance: 3.5 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 30 | LED type: IR/White | Number of illumination LEDs: 4 | Maximum resolution: 4480 x 2512 | Total megapixels: 12 | Video compression formats: H.264/H.264+/H.264B/H.264H/H.265/H.265+/M-JPEG | Supported graphics resolutions: 1280 x 960/2304 x 1296/2688 x 1520/2880 x 1620/3072 x 1728/3072 x 2048/352 x 240/352 x 288/3840 x 2160/704 x 480/704 x 576 | Supported video modes: 1080p/1296p/1520p/1536p/1620p/2160p/240p/2880p/480p/576p/720p/960p | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: H.264: 32 kbps-8192 kbps; H.265: 12 kbps-8192 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Digital Wide Dynamic Range (DWDR): Yes | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Built-in microphone: Yes | Number of microphones: 1 | Voice codecs: G.711a/G.711Mu/G.726/PCM | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; P2P; Bonjour; Auto Registration | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Client interoperability: ONVIF (Profile S & Profile G & Profile T); CGI | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | ROM capacity: 128 | RAM capacity: 512 | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Intrusion/Tripwire | Video motion detection: Yes | Power source type: DC,PoE | Power consumption (typical): 3.1 | Power consumption (max): 10.1 | Power consumption (Power over Ethernet (PoE)): 3.7 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Width: 90.7 | Height: 90.7 | Length: 238.5 | Weight: 720 | Package weight: 970 | Number of cameras: 1 | Audio input: RCA | Audio output: RCA | Browser supported: IE; Chrome; Firefox | Data transfer rate: 100 | Iris: Yes | Lens mount interface: M12 | Unit Calculated Weight: 1 | Product Net Weight: 0.72 | Unit Calculated Volume: 0.004104 | Units per Shipping Box: 1 | Unit Width: 12 | Units per Pallet: 0 | Shipping Box Height: 12 | Unit Depth: 28.5 | Unit Height: 12 | Name: NET CAMERA 12MP BULLET/HFW21249T-AS-IL-0280B DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950