

Set of 2x EcoFlow 250W photovoltaic panel Rigid design



Model: EFSOLAR250W-R-D-LF-1

Manufacturer: ECOFLOW

EAN: 4895251642002

Product Code: 815300

R22,422

Set of 4x EcoFlow 250W Photovoltaic Panel Rigid Construction

EcoFlow 250W W solar panels are the perfect solution for anyone who wants to reduce electricity bills and become independent from rising energy costs. Thanks to their sturdy, rigid construction and high efficiency, the panels allow you to generate energy even in low sunlight - they are ideal for use in the garden, on the balcony or on the roof. The package contains 4 pieces of the product.

High efficiency

With a conversion factor of 25% and a high output of 250WW, EcoFlow panels are able to produce energy even in low light - such as on cloudy mornings or winter days.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Weather resistance

The panels are designed to withstand the elements. They offer certified IP68 water resistance, which means full protection from dust and rain. That's confidence in performance no matter what the weather.

Tailor the system to your needs

EcoFlow 250W panels can operate as part of the larger STREAM ecosystem, whose capacity can be scaled from 1.92 to as much as 11.52 kWh. This gives the user the ability to expand the entire energy storage system as needed, from simple balcony installations to complex whole-house power supply.

Manufacturer	EcoFlow
Model	EFSOLAR250W-R-D-LF-1
Rated power	250 W
Construction type	Rigid Panel
Conversion factor	25%
Open circuit voltage (Voc)	50 V
Short-circuit current (Isc)	6,3 A
Optimum operating voltage (Vmp)	43V
Optimum operating current (Imp)	5,9 A
Recommended ambient temperature	-20°C to 85°C
Temperature coefficient of rated power	-0,30%/°C
Temperature coefficient of open circuit voltage	-0,25%/°C
Temperature coefficient of short-circuit current	+0,04%/°C
Maximum system voltage	150V DC (IEC/UL)
Protection class	IP68
Weight	Approximately 10 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Dimensions	1157 × 1165 × 20 mm
Cell type	TOPCon monocrystalline silicon
Connector type	LFB-30
Number of pieces in set	4

Type: Rigid, Rated power (W): 250, GPSR Link: https://psr-assets.innpro.pl/energy/sg_energy_photovoltaiiv_panels.pdf, Gross weight: 46900, Net weight: 40800, Box length: 128,00, Box width: 119,50, Box height: 13,70, Last delivery: 01.09.2026, test: Zestaw 4x Panel fotowoltaiczny EcoFlow 250W Sztywna konstrukcja, GARAN: <https://garan.innpro.pl/ecoflow/4895251642002>

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950