

Tenda TX12L Pro wireless router Gigabit Ethernet Dual- band (2.4 GHz 5 GHz) Black



Model: TX12L Pro

Manufacturer: TENDA

EAN: 6932849424317

Product Code: 820276

R1,524

Certification: CE, FCC, RoHS | VPN support: IPSec Transparent Transmission PPTP Transparent Transmission L2TP Transparent Transmission PPTP VPN Server PPTP VPN Client L2TP VPN Client | Width: 244 mm | AC input voltage: 100 - 240 V | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 10 | Depth: 56 mm | Modulation: OFDMA | Product colour: Black | Quick installation guide: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Modulation: 1024-QAM | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN: Yes | DHCP client: Yes | Operating relative humidity (H-H): 10 - 90% | Processor frequency: 1300 MHz | Antennas quantity: 5 | Operating temperature (T-T): 0 - 40 °C | Ethernet WAN: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | AC adapter included: Yes | Cables included: LAN (RJ-45) | Reset button: Yes | Filtering: Yes | Security algorithms: WPA3-SAE | Security algorithms: WPA2-PSK | Ethernet LAN (RJ-45) ports: 3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

| Storage relative humidity (H-H): 5 - 90% | Wi-Fi standards: 802.11g | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | WLAN data transfer rate (max): 2402 Mbit/s | Ethernet LAN interface type: Gigabit Ethernet | Security algorithms: WPS | Power source type: DC | Wi-Fi standards: 802.11b | Networking standards: IEEE 802.3u | Ethernet LAN data rates: 100 | Output voltage: 12 V | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | WPS push button: Yes | Universal Plug and Play (UPnP): Yes | Dynamic DNS (DDNS): Yes | Guest access: Yes | Static route: Yes | Height: 200 mm | Port forwarding: Yes | Firewall security: ICMP Flood Attack Defense, TCP Flood Attack Defense, UDP Flood Attack Defense, Block Ping From WAN | DHCP server: Yes | DMZ support: Yes | Built-in processor: Yes | Output current: 1 A | Number of products included: 1 pc(s) | USB port: No | Firewall: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | WLAN data transfer rate (first band): 574 Mbit/s | Internal memory: 256 MB | Product type: Tabletop router | VPN server: Y | WLAN data transfer rate (second band): 2402 Mbit/s | MU-MIMO technology: Yes | Bandwidth control: Yes | URL filtering: Yes | Maximum Tx power (5 GHz): 23 dBmW | Antenna design: External | Maximum Tx power (2.4 GHz): 20 dBmW

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950