



Power Supply
XILENCE 550
Watts Efficiency
80 PLUS
BRONZE PFC
Active XN215

Model: XN215

Manufacturer: XILENCE

EAN: 4044953501685

Product Code: 822257

R1,644

The new successful Gaming series combines high performance with a low noise level and high efficiency. The new DC/DC technology guarantees for increased efficiency and a maximum tension stability even during excessive gaming. Thanks to this high efficiency and the associated 80+ BRONZE certification high electricity costs are now a thing of the past. Six integrated safety circuits provide for an all-time safe operation and the sleeved main cable harness ensures order in the PC case.

- Extremely silent cooling: large 120mm fan
- semi-modular cable management
- Excellent air flow design for a better heat dissipation

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Low stand-by consumption
- High energy efficiency: 80+ BRONZE certified (complies with ErP2014 norm)
- Active-PFC

Summary: Xilence Performance A+ XN215. Total power: 550 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, WEEE | Vendor Homepage: <https://www.xilence.net/en/power-supplies/121> | Total power: 550 | AC input voltage: 200 - 240 | AC input frequency: 50 | Input current: 10 | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 105 | Combined power (+12V): 456 | Max output current (+3.3V): 21 | Max output current (+12V): 38 | Max output current (+5V): 16 | Max output current (-12V): 0.5 | Max output current (+5Vsb): 2.5 | Power protection features: Over power/Over voltage/Short circuit/Under voltage | Motherboard power connector: 20+4 pin ATX | Motherboard power cable length: 500 | Number of SATA power connectors: 6 | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 2 | CPU power connector (4+4 pin): Yes | ATX power connector (20+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 1 | PCI Express connector: Yes | Cabling type: Non-Modular | 80 PLUS certification: 80 PLUS Bronze | Purpose: PC | Power supply unit (PSU) form factor: ATX | ATX version: 2.4 | Bearing technology: FDB | Product colour: Black | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | Fan location: Top | On/off switch: Yes | Compliance certificates: RoHS/WEEE | Package weight: 1890 | Package type: Box | Sustainability certificates: ErP | Unit Calculated Weight: 1.95 | Product Net Weight: 1.6 | Unit Calculated Volume: 0.0066 | Units per Shipping Box: 8 | Unit Width: 16 | Units per Pallet: 0 | Shipping Box Height: 24 | Unit Depth: 25 | Unit Height: 10 | Name: CASE PSU ATX2.4 550W/XP550R10 XN215 XILENCE | Model name: XN215 | XP550R10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950